

MAINTENANCE SYSTEM SHEET Passenger Cars (ISA) M.Y.'s 1986 – 1997 Including MY 98 SLK w/o "flexible" maintenance



Dealer Name: Technician:			Dealer Code:	Customer Name:				
			R.O. Number:	Year & Model:			Mileage:	
107	124	126	129	140	170	201	202	210
Shaded	areas indicat	e additional	work to be per	formed to	gether with	respective M	laintenance 5	Service.
INSPECT	TION SE	RVICE		••••••				
All Models	M.Y. 1992 →	1 995: Once	00 – 1,000 mile e at 800 – 3,00 service not rec	0 miles/1,	- 1,600 km. 300 – 4,800) km.		
		If jo	b no. required		ditional ser		Ма	intenance Job No.
Wheels a	nd tires		p.oacoo					002 110.
	k, correct tire nten wheel bo		e tightening to	rque!				4060 4070
Underside	e of car							
_	•		mount (4MAT	IC only)				2291
	al transmission fer case fluid	_						2601 2801
Rear	axle oil chan	ge	,,					3501
	<i>tightening to</i> tighten steeri	•	s (except mode	al 140)				4671
	tighten steen tighten exhau		s (except mode	51 140)				4970
	tighten exhau	ıst system c	onnections					4971
Engine co	ompartme	nt						
	e oil and filte	-	f V-belts 1) (eng	ainos 116	and 117\			0101 1350
	nd correct flu		i A-neita v (eni	giries 110	anu 117)			1550
=	gine coolant		/ 143/ 400/	- \				2011
☐ Aut	tomatic trans /el control, A		(→ M.Y. 1990 MATIC fluid	3)		片		2710 3211
☐ Bra	ake fluid	DO, 70D, 41	VIATIO IIdia					4210
Por	wer steering		1000)					4611
	ttery electroly ndshield was		1990)					5410 8210
Trunk								
☐ Checl	k, correct tire							4060
☐ Checl	k and correctels 124.090/0		v washer fluid I	evel				8210
☐ Checl	k and correct	hydraulic so	oft top fluid leve	əl				7710

(models 124.066, 129)

LUBRICATION SERVICE

All Diesel models except 140.134, 124.131, 210.020: Every 5,000 miles/8,000 km, or at least once a year. **All other models incl. 140.134, 124.131, 210.020:** Every 7,500 miles/12,000 km, or at least once a year.

For Severe Operating Conditions, please refer to the respective Maintenance Booklet.

	If job no. required ANY additional serv please note on R.O. and check		Maintenance Job No.
Engi	ne compartment		005 110.
	Engine oil and filter change Reset Maintenance Service Reminder		0101
	Inspect, lubricate throttle linkage (→ M.Y. 1995)		3022
片	Check and correct battery electrolyte level (→ M.Y. 1990) Lubricate hood hinges		5410 8821
	Reset Maintenance Service Reminder (model 170.447)		332.
Und	erside of car		
	Adjust engine stop, rear engine mount (4MATIC only) Once at 7,500 miles/12,000 km		2291
MAI	NTENANCE SERVICE		
	odels: Every 15,000 miles/24,000 km or every 2 years.		
	If job no. required ANY additional serv please note on R.O. and check		Maintenance Job No.
	Brake test, parking brake check		4290
	4MATIC vehicles, observe 🗥 WARNING! in Maintenance Manual		
Inter	ior		
	Check warning and indicator lamps, horn		5451
	Clean cassette deck tape head Inspect headlamps and exterior lamps (incl. Daytime Running		8230
ш	Lamps (Incl. Baytime Harring		8251
	Inspect/test windshield, rear window and headlamp	r 	0050
	wiper/washer system Heating and ventilation: Replace dust filter (models 202, 210)		8252 8381
	Inspect seat belts for damage		9150
	Backrest lock, check operation (models 124.05/06, 140.070/076)		9151
	Every 45,000 miles/72,000 km (→ M.Y. 1993) Every 45,000 miles/72,000 km or 2 years (M.Y. 1994 →)		
m	Replace air recirculation filter (model 140)		8383
	Replace activated charcoal filters (model 210)		8382
Body	V		
	Lubricate door hinges (models 107, 126)		7220
	Lubricate door locks (models 107, 126)		7221
	Soft top locking lugs, check for wear (model 129) Clean antenna mast with special cleaning cloth		7750 8231
	Check condition of headlamp wiper blades		8252
	Replace windshield wiper insert(s)		8280
	Every Two Years		
	Clean water drains (→ M.Y. 1993)		6030
	Clean and lubricate sliding roof rails (→ M Y 1993)		7730 0850
Ш	Inspect body for paint damage	Ш	9850
	Every Three Years		
	Clean and lubricate sliding roof rails (M.Y. 94, except model 210		7730

	If job no. required ANY additional serv		Maintenance
Wh	please note on R.O. and check neels, tires & brakes	K 🖾	Job No.
	Inspect, rotate wheels (please note specific instructions in Maint. Manual regarding models 140.070/076 M.Y. 95, 129.063/067/076		4050
П	with AMG Sport Package, 170.447, 202.028 [C36 AMG]) Inspect tires and record tread depth	H	4050 4051
	Correct tire pressure		4060
	Check brake pad/disk thickness, check condition of discs		4251
Ш	Adjust parking brake (except models 140, 202, 210) Once at 15,000 miles/24,000 km (model 129)	Ш	4261
	Every Two Years		
	Replace brake fluid		4280
Un	derside of car		
	Inspect condition, routing, leaks, of components, lines and hoses		0053
	Check and correct fluid level:		
	Manual transmission fluid Transfer case fluid (4MATIC only)		2610 2810
H	Transfer case fluid (4MATIC only) Front axle fluid (4MATIC only)	H	3310
	Rear axle oil (\rightarrow M.Y. 1993)	H	3510
	Check front axle ball joints		3353
	Check steering play		4650
	Retighten steering gear bolts (→ M.Y. 1991)		4671
	Every Two Years		
	Inspect suspension and body structure		0090
	Every 30,000 miles/48,000 km		
	Check clutch disc for wear		2551
	Automatic transmission fluid and filter change (except [M.Y. 1996]		2702
_	models 140.043/051/057/070/076, 129.067/076, [M.Y. 1997 → ALL]	l)	4450
\sqcup	Inspect drive shaft flex discs	H	4152 4256
H	Inspect parking brake cables (except models 140, 202, 210) Retighten steering gear bolts (M.Y. 1992 →)	\forall	4256 4671
	(except models 140, 210) Observe tightening torque!	L	4071
	Every 60,000 miles/96,000 km		
	Replace fuel filter (except engines 102, 104, 119, 120 ²⁾)		0780
	Check front axle ball joint freeplay (Models 124, 129, 201)		3355
End	gine compartment		
\Box	Inspect condition, routing, leaks, of components, lines and hoses	П	0053
	Engine oil and filter change		0101
_	Reset Maintenance Service Reminder		
	Check valve clearance (engine 102.983)	닏	0561
	Check injection timing (engines 602 and 603) Once at 15,000 miles/24,000 km (M.Y. 1990 → 1994)	Ш	0760
	Check condition and tension of V-belts 1) (engines 116 and 117)	П	1350
	Inspect poly-V-belt 1)		1351
	Check spark plugs, replace if necessary 1)		1550
	Replace spark plugs. Federal version (→ M.Y. 1987)		
	Check and correct fluid level		0010
\vdash	Engine coolant/antifreeze protection Automatic transmission fluid (→ M.Y. 1993)	님	2010 2710
\forall	Level control, ADS, ASD, 4MATIC fluid	\exists	3211
	Brake system		4210

Check and correct fluid level (continued)	If job no. required ANY additional service please note on R.O. and check ⊠				
Power steering fluid					
Check injection timing (Diesel engines)	 □ Power steering fluid □ Battery electrolyte (except models 124.034/036, 129, 140, 202, 210) □ Windshield washer fluid □ Inspect, lubricate engine throttle linkage □ Check A/C refrigerant charge (except model 210) □ Replace ventilation system dust filter 		4611 5410 8210 3022 8312		
Every 60,000 miles/96,000 km Replace oxygen sensor. Once at 60,000 miles/96,000 km [model 201,028 California version only) Replace fuel filter (Diesel engine only) (M.Y. 1996 →)	Check injection timing (Diesel engines) Once at 30,000 miles/48,000 km (M.Y. 1995 →) Replace fuel filter (Diesel engines only) (→ M.Y. 1995) Replace air cleaner element (all engines → M.Y. 1995) Check condition and tension of V-belts 1) (→ M.Y. 1991) (engines 116 and 117) Inspect poly-V-belt (→ M.Y. 1991) Replace spark plugs Every 45,000 miles/72,000 km (→ M.Y. 1993) Every 45,000 miles/72,000 km or 2 years (M.Y. 1994 →)		0760 0780 0781 0980 1350 1351 1580		
Replace coolant (water/anticorrosion/antifreeze mixture) 2080	Every 60,000 miles/96,000 km Replace oxygen sensor. Once at 60,000 miles/96,000 km (model 201.028 California version only) Replace fuel filter (Diesel engine only) (M.Y. 1996 →) Replace fuel prefilter (Diesel engine only) (M.Y. 1996 →) Replace air cleaner element (M.Y. 1996 →) Every 75,000 miles/120,000 km (→ M.Y. 1993) Every 75,000 miles/120,000 km or 4 years (M.Y. 1994 →)		1480 0780 0781 0980		
Hydraulic soft top fluid	Replace coolant (water/anticorrosion/antifreeze mixture) Battery electrolyte level (except maintenance-free batteries) Trunk Correct tire pressure (spare) Check and correct fluid level: Rear window washer fluid (models 124.090/092/193/290)		8210		

¹⁾ Mercedes-Benz urges that this procedure be performed to maintain peak performance, although it is not required to maintain your emission warranty and will not affect Mercedes-Benz's recall liability.

²⁾ Replacement is not required at 60,000 miles on California version vehicles 1).