

## Fuels, Coolants, Lubricants, etc. Capacities

Vehicle components and their respective lubricants must match. Therefore use only brands tested and recommended by us. Inquire at your authorized MERCEDES-BENZ dealer.

	Capacity	Fuels, coolants, lubricants, etc.
Engine with oil filter	8.0 l (8.5 US qt)	<p>Recommended engine oils</p> <p>Ambient temp.   SAE grades</p> <p>°F   °C</p> <p>86   30 68   20 50   10 32   0 23   5 14   10 5   15 4   20</p> <p>5W-20 5W-30 10W-30 20W-40 20W-50 30<sup>1</sup> 15W-40 15W-50 10W-40 10W-50</p> <p>8938</p> <p><sup>1</sup> SAE 40 may be used if ambient temperature constantly exceed +30 °C (+86 °F).</p>
Automatic transmission	Initial fill: 8.6 l (9.1 US qt) Fluid change: 7.7 l (8.1 US qt)	MB Automatic transmission fluid

	Capacity	Fuels, coolants, lubricants, etc.
Rear axle	1.3 l (1.4 US qt)	Hypoid gear oil SAE 90 for limited slip differential <sup>1</sup>
Accelerator control linkage		Hydraulic fluid <sup>1</sup>
Power steering	1.3 l (1.4 US qt)	MB Power steering fluid
Front wheel hubs	approx. 65 g (2.3 oz) each	High temperature roller bearing grease
Grease nipples		Multipurpose or lubrication grease
Door locks		Powdered graphite
Battery terminals		Bosch special grease (acid proof)
Brake reservoir	approximately 0.5 l (0.5 US qt)	MB Brake fluid (DOT4)
Windshield washer system	approximately 5.0 l (5.3 US qt)	MB Windshield washer concentrate "S" <sup>2</sup>
Fuel tank including a reserve of	approximately 85 l (22.5 US gal) approximately 11.5 l (3.0 US gal)	Premium unleaded gasoline: Posted Octane 91 (Average of 96 RON/86 MON)
Cooling system	13.0 l (13.7 US qt)	MB Anticorrosion/antifreeze

<sup>1</sup> Your authorized MERCEDES-BENZ dealer will advise you on recommended brands.

<sup>2</sup> Use MB Windshield Washer Concentrate "S" and water for temperatures above freezing or MB Windshield Washer Concentrate "S" and commercially available premixed windshield washer solvent/antifreeze for temperatures below freezing. Follow suggested mixing ratios, on page 41.