TO: Mercedes-Benz Principals, General Managers, Sales Managers, Service Managers, Parts Managers	FROM: Anthony Washington, Department Manager, Regulations and Certifications
Re: Recall Campaign Launch Notification Models 907 (Sprinter) Model Years 2019-2020 Remove Power Sliding Door Function *UPDATE #2*	DATE: July, 2023

IMPORTANT RECALL CAMPAIGN INFORMATION

Please see the attached documents related to the campaign listed above

Please note that electric sliding door function will be removed with this campaign.

Please refer to following pages (CLICK) for specific work instructions for applicable options.

Page 4

with code EL9 (Two-way loudspeaker system in front and rear)
with code ZU8 (National version for USA)
with T55 (electric actuation of right sliding door)
Page 40
with code ZU8 (National version for USA)
WITHOUT code EL9 (Two-way loudspeaker system in front and rear)
with T55 (electric actuation of right sliding door)
Page 78
with code EL9 (Two-way loudspeaker system in front and rear)
with code ZU8 (National version for USA)
WITHOUT code EL9 (Two-way loudspeaker system in front and rear)
with code ZU8 (National version for USA)
with T50 (electric closing assist of right sliding door)
Page 108
with code ZU8 (National version for USA)
WITHOUT code EL9 (Two-way loudspeaker system in front and rear)
with code ZU8 (National version for USA)
WITHOUT code EL9 (Two-way loudspeaker system in front and rear)
with code ZU8 (National version for USA)

\bigcirc

Mercedes-Benz USA, LLC

News Channel Update | Vans Customer Service and Parts

Campaign No. :	Campaign	Desc. :	
2022120001	VS3SCHI	Remove Power Sliding Door Function	
Mercedes-Benz Sprint	This is to notify you of a Recall Campaign Launch to remove power sliding door function on approximately <u>56</u> MY19-20 Mercedes-Benz Sprinter vans. The recall campaign will be visible on the <u>www.safercar.gov</u> website and may generate questions from customers. All affected VINs will be flagged " OPEN " in VMI and <u>cannot be sold</u> until remedied.		
	Γ	Ва	ackground
Issue	Mercedes-Benz AG ("MBAG"), the manufacturer of Mercedes-Benz vans, has determined that certain Sprinter vehicles from platform 907 (VS30) that are equipped with an optional electric sliding door may have been manufactured with an auxiliary lock on the sliding door that was not specified for use in connection with an electric sliding door. Affected vehicles that have this auxiliary lock may show an increased outward displacement of the sliding door in the event of a crash, which could increase the risk of injuries for vehicle occupants in a crash. As a result, the auxiliary locks do not comply with FMVSS 226 (<i>Ejection Mitigation</i>).		
What We're Doing	MBUSA will conduct a voluntary recall campaign. An authorized Mercedes-Benz Sprinter dealer will convert the electric sliding function of the sliding door into a manual function for which the installed auxiliary lock is specified.		
Dorte	Part numbers are		
Parts	Place order base	d on the code r	rule (4 different variations available)
	1	Veh	nicles Affected
Vehicle Model Year(s)	Model Year(s) 2019-2020		
Vehicle Model (s)	Vehicle Model (s) Sprinter(907)		
		Vehi	cle Populations
Total Recall	56		
Dealer Inventory	0		
Given this notice, it is			ler to sell or lease any <u>new</u> vehicles in dealer inventory covered by
	this r	notification until	the vehicle has been repaired.
Loaner a	nd demonstrator ve	hicles may conti	nue to be driven, but must not be retailed until repaired.
Additionally, give			eral Law for rental companies to rent new vehicles covered by this the vehicle has been repaired.
Next Steps/Notes			
Customer Notificat	ion Timeline	An owner notif	ication letter will be mailed in January 2023.
AOMS/SOMS	AOMS/SOMS AOMs – This recall may generate questions from your dealers. Please forward this notice to your dealers ASAP.		
Rental Fleet Partne	Rental Fleet PartnersThis recall may affect vehicles in your fleet. Please contact your respective MBUSARental Fleet Partnersfleet representative for further information and next steps. For repairs, please contact your preferred MBUSA dealer.		tative for further information and next steps. For repairs, please
While we regret any inconvenience this may cause, we are determined to maintain a high level of vehicle quality and customer satisfaction.			

Mercedes-Benz USA, LLC

A Mercedes-Benz AG Company



Recall Campaign Bulletin

Campaign No. 2022120001, December, 2022

TO: ALL MERCEDES-BENZ CENTERS

SUBJECT: Model 907 Sprinter, Model Year 2019-2020 Remove Power Sliding Door Function

Mercedes-Benz AG ("MBAG"), the manufacturer of Mercedes-Benz vans, has determined that certain Sprinter vehicles from platform 907 (VS30) that are equipped with an optional electric sliding door may have been manufactured with an auxiliary lock on the sliding door that was not specified for use in connection with an electric sliding door. Affected vehicles that have this auxiliary lock may show an increased outward displacement of the sliding door in the event of a crash, which could increase the risk of injuries for vehicle occupants in a crash. As a result, the auxiliary locks do not comply with FMVSS 226 (Ejection Mitigation).

MBUSA will conduct a voluntary recall campaign. An authorized Mercedes-Benz Sprinter dealer will convert the electric sliding function of the sliding door into a manual function for which the installed auxiliary lock is specified.

Prior to performing this Recall Campaign:

- Please check VMI to determine if the vehicle is involved in the Campaign and if it has been previously repaired.
- Please review the entire Recall Campaign bulletin and follow the repair procedure exactly as described.

Please note that Recall Campaigns **do not expire** and may also be performed on a vehicle with a vehicle status indicator.

Approximately **56** vehicles are involved.

Order No. V-RC-2022120001 This bulletin has been created and maintained in accordance with MBUSA-SLP S423QH001, Document and Data Control, and MBUSA-SLP S424HH001, Control of Quality Records.

Reacll Campaign Bulletin





Work instructions

Van

Group 72 CODE: VS3SCHIEBT

> SM72.16-D-0008A 16.05.2023

Sliding door conversion (code: VS3SCHIEBT, acc. no.: 72 951 62)

Model 907.6/7 with code EL9 (Two-way loudspeaker system in front and rear) with code ZU8 (National version for USA) with electric actuation of right sliding door

© 2023 by Mercedes-Benz AG Printed in Germany This document, including all its parts, is protected by copyright. Any further processing or use requires the previous written consent of Mercedes-Benz AG, Department GSP/OR, D-70546 Stuttgart. This applies in particular to reproduction, distribution, alteration, translation, microfilming and storage and/or processing in electronic systems, including databases and online services.

SM72.16-D-0008A	Sliding door conversion (code: VS3SCHIEBT, acc. no.: 72	05.05.2023
	951 62)	

Model 907.6/7

with code EL9 (Two-way loudspeaker system in front and rear) with code ZU8 (National version for USA) with electric actuation of right sliding door

Operation no. of the operation texts or standard texts and flat rates

Category O	Dp. no.	Operation text	Time	Damage Code	Code
L 02		Operations: Modify sliding door on vehicle with code T55/EL9/V40	6.5 hrs	72 951 62	VS3SCHIEB T

Important!
On the affected vehicles, the sliding door is converted from electrical to mechanical actuation.
Replacement parts ordering:
Before ordering the required replacement parts, the special equipment code T55 (Electrical actuation for right sliding door) must be removed from the Vehicle Documentation (VeDoc). Only then can the correct replacement parts can be determined using XENTRY Parts Information.
Vehicle documentation (VeDoc):
Changes in VeDoc can only be made by users with write permission.
If no-one with change authorization is available, a ticket must be created in the "XENTRY Support and Feedback (XSF)" system for "Vehicle data/VeDoc".
Please note that the XSF ticket has to be approved by the national organization, something which involves additional processing time.
It may take a few days for the entry to be visible in VeDoc.
In the event of problems:
If problems arise while carrying out the service measure, please create a PTSS case.
To do this, use the "DTS pre-case checklist".
The most recent version is always available via the XENTRY Portal.



Shown on vehicle with automatic transmission

- 1 Stowage compartment
- 2 Switches

Shown on vehicle with code T74 (Grab handle for entrance)

- 5 B-pillar paneling
- 6 Switches
- 7 Connector


3 Connector



D72.16-A043-76



- 8 Closing assist motor electrical wiring harness
- 36 Retaining bolt
- 37 Guide rail



D72.16-A058-80

A Warning	Risk of injury caused by fingers being jammed or pinched when removing, installing or aligning hoods, doors, trunk lid/rear-end door or sliding roof.	No parts of the body or limbs should be within the operating area when the components are moving.	AS00.00-Z-0011-01A
▲ Caution	Risk of injury caused by scraping or cutting body parts on sharp vehicle parts	Always wear protective gloves when working on or near sharp and non-deburred vehicle parts. Deburr repair panels.	AS00.00-Z-0017-01A
Notice	Information on preventing damage to electronic components due to electrostatic discharge		AH54.00-P-0001-01A
Notice	Notes on carrying out repair work in the vehicle interior		AH68.00-D-0001-01KOS
Notice	Notes on retrofitting electrical/ optical lines		AH82.00-P-0000-01A


	Check		
1	Check if vehicle is affected by measure.		
	Update Vehicle Documentation (VeDoc)		
2	Remove special equipment from online vehicle data card.	i Remove existing code T55 (Electrical actuation for right sliding door).	
3	Attach "Sliding door converted as per SM72.16-D-0008A note" under field organization texts to KG72.		
X	Remove		
4	Detach ground line of on-board electrical system battery.		
⊯ AR			AR54.10-D-0029TS
5	Remove component parts in vehicle interior for sliding door conversion.		Page 10
6	Remove stowage compartment (1) with switch (2) for electric sliding door.		
₩ F AR		i The stowage compartment (1) and switch (2) are no longer required. Information on wiring diagram: Right stowage compartment sliding door pushbutton switch (S169/2)	AR68.10-D-1513TS
7	Strap down plug (3) of switch (2) using cable ties on factory- installed electrical wiring harness or at a suitable point.	i The plug (3) is no longer required.	
8	Remove B-pillar trim (5) on front passenger side with switch (6) for electric sliding door.		
₩ AR		Model 907.6/7 i The B-pillar trim (5) and switch (6) are no longer required. Information on wiring diagram: Right sliding door button (S159/8)	AR68.30-D-4706TS

[_			
9	Strap down plug (7) for switch (6) using cable ties on factory- installed electrical wiring harness or at a suitable point.	i The plug (7) is no longer required.	
10	Remove closing assist motor with lock striker in C-pillar.		
Ĩ₩ĨAR		i The closing assist motor is no longer required.	AR72.16-D-0002TSR
11	Remove lower guide rail for sliding door.		
⊯FAR		Model 907.6/7 i The lower carriage is no longer required.	AR72.16-D-7816TS
12	Remove closing assist motor electrical subharness (8).	i To do so, unclip electrical subharness (8), guide it out of C- pillar then disconnect electrical connector.	
		The electrical subharness (8) is no longer required.	
		S Clip remover	452 589 01 63 00
13	Remove sliding door.		
₩ĨAR		Model 907.6/7	AR72.16-D-1260TSB
	Modify sliding door		
14	Remove switch for deactivation of electric sliding door.		
₩ AR		i The switch is no longer required.	AR72.16-D-0003TSR
15	Remove motor for electric sliding door with cable.		
₩ F AR		i The engine and cable are no longer required.	AR72.29-D-5901TS
16	Remove electric sliding door control unit.		
₩AR		i The control unit is no longer required.	AR72.29-D-5898TS
17	Remove anti-entrapment strip for electric sliding door.		
₩ĨAR			AR72.29-D-5890TS


18	Remove center carriage for sliding		
10	door.		
₩ AR		Model 907.6/7	AR72.16-D-2230TSB
19	Remove the lock for the sliding door.		
₩ĨAR		Model 907.6/7	AR72.16-D-4035TSB
20	Install new sliding door lock.		
₩ AR		Model 907.6/7	AR72.16-D-4035TS
		i Install outside door handle cable only. Do not attach remaining cables.	
21	Retrofit electrical wiring harness in sliding door.		Page 29
22	Remove door handle.		
₩ AR			AR72.16-D-6601TS
		i Only remove door handle far enough to gain access to cables.	
23	Modify cables in sliding door.		Page 29
		i Operation steps 3 to 9 of document reference.	
24	Modify detachable parts on sliding door.		Page 29
		i Operation steps 10 to 17 of document reference.	
25	Install new center sliding carriage of sliding door.		
₩ĨAR		Model 907.6/7	AR72.16-D-2230TS
	Retrofit wiring harness in vehicle interior		
26	Fabricate wiring harness for sliding door.		
F¥PE	Wiring diagram for sliding door		PE72.16-D-2001LAA
			Page 18
07		S Wiring harness repair kit, basic	000 589 13 99 00
27	Retrofit wiring harness for sliding door.		
₩₹₩S	000 588 00 84 00 Heat gun		WS54.00-P-0049B
₩ĨAR	Repairing wiring harness using solder connectors		AR00.19-P-0100-09A
₩ ₽ ₽E	Wiring diagram for sliding door		PE72.16-D-2001LAA
F¥PE	Wiring diagram for loudspeakers		PE82.62-D-2102LAA
			Page 21
		S Reflector	220 589 01 99 41
		S Adapter	220 589 01 99 42
		S Wiring harness repair kit, basic	000 589 13 99 00

X	Install		
28	Attach new retaining bolt (36) to new lower guide rail (37).	i 20 Nm	
29	Install new lower sliding door carriage.		
₩FAR		i New lower carriage is supplied with flexible power duct and cable.	AR72.16-D-7844TSA
30	Install new lower guide rail (37).		
₩ F AR			AR72.16-D-7816TS
31	Retrofit reinforcement for lock striker in C-pillar.		Page 16
32	Install sliding door.		
⊯ AR		Model 907.6/7	AR72.16-D-1260TS
33	Adjust sliding door.		
⊯ AR			AR72.16-D-1023TS
34	Install new B-pillar trim on front passenger side.		
₩ĨAR		Model 907.6/7	AR68.30-D-4706TS
35	Install new lower center stowage compartment on instrument panel.		
₩ĨAR			AR68.10-D-1513TS
36	Install removed component parts in vehicle interior for sliding door conversion.		Page 10
37	Connect ground line of on-board electrical system battery.		
⊯FAR			AR54.10-D-0029TS
	SCN coding		
38	Connect diagnostic system.		
⊯≊AD			AD00.00-D-2000-06TS
		i It is absolutely essential to precisely follow the operation steps as described in the vehicle diagnosis system.	


39	Connect charging equipment.		
⊯ AR			AR54.10-D-1127TS
		During the entire work procedure a sufficiently large voltage supply must be provided for the vehicle's on-board electrical system.	
		Otherwise any undervoltage that occurs may damage the control units.	
		i Follow the operating instructions for the charger.	
		i	
		Use the charger to ensure that an adequate power supply (min. 12.5 V) is provided for the on-board electrical system battery.	
40	Perform SCN coding on signal acquisition and actuation module (SAM) control unit.		
₩			AR54.21-D-0015TS
		i Under the "Control unit adaptations" menu item, follow the instructions for "SCN coding".	
41	Remove charger from vehicle.		
₩ĨAR			AR54.10-D-1127TS
4	Check		
42	Check sliding door for correct opening and closing.	i See Operator's Manual.	
43	Perform key function test.	i See Operator's Manual.	




Adapter



Reflector



Wiring harness repair kit, basic



Clip remover


Parts	ordering	note
-------	----------	------

Part no.	Designation	Quantity
A 907 540 8965 08	Electrical wiring harness for manual sliding door for vehicles WITH EL9	1
A 906 630 33 00	C-pillar	1
A 910 763 01 00	Sliding base in center	1
N 000000 001152	Screw	2
A 906 720 02 04	Lock striker	1
A 000 984 31 29	Screw	2
A 910 730 39 00	Door lock (bottom)	1
A 910 998 00 50 9051	Cover Plug	n.B.
A 907 730 42 00	Cable	1
A 910 760 15 00	Cable	1
A 910 760 16 00	Cable	1
A 000 995 51 14	Line fastener	5
A 907 820 38 00	Sliding base bottom	1
N 000000 000455	Screw	2
A 910 683 18 00	Stowage tray	1
A 906 691 01 33 9051	Сар	1
A 907 631 02 00	Bracket	1
A 907 690 36 00 9051	Right sliding door B-pillar trim, grab handle	1
A 906 692 12 22	Cover (on vehicle with code V36 Roof lining)	2
A 906 692 07 22 9051	Cover	1
A 910 998 02 50 9051	Cover plug	n. B.
A 906 686 34 07 9E80	Cover plug	1
A 110 987 05 44	Plug	1
A 906 998 0050	Cover Plug	1
	Parts for electrical wiring harness:	
	Electric lines (available on free market, observe specifications)	4
A 013 545 76 26	Female contact	1
A 001 982 57 02	Cable lug (ground connection)	1
A 001 545 59 80	Blanking Plug	4
A 009 545 81 26	Female contact	4
A 000 545 71 80	Seal	4
A 000 995 25 94	Cable tie	n. B.
A 007 989 28 85	Fabric tape	n. B.

SM72.16-D-0009SG	Prepare vehicle interior at front for sliding door conversion	
	(code: VS3SCHIEBT, acc. no.: 72 951 62)	

Model 907

with code ZU8 (National version for USA)



51 Control unit bracket 52 Nut

D54.21-A026-09

Shown on model 907.7 without S23 (Front passenger bench seat)


- 10 Cover
- 11 Nuts
- 12 Air duct



D31.19-1216-12

Shown on model 907.7 without S23 (Front passenger bench seat)

- 15 Air duct
- 16 Nuts
- 17 Cable duct
- 18 Bolts
- 19 Battery cover
- 20 Cover



D31.19-1217-06

<u>∧</u> Warning	Risk of injury caused by fingers being jammed or pinched when removing, installing or aligning hoods, doors, trunk lid/rear-end door or sliding roof.	No parts of the body or limbs should be within the operating area when the components are moving.	AS00.00-Z-0011-01A
<u> </u>	CautionRisk of injury caused by scraping or cutting body parts on sharp vehicle partsAlways wear protective gloves when working on or near sharp and non-deburred vehicle parts.		AS00.00-Z-0017-01A
		Deburr repair panels.	
Notice	Information on preventing damage to electronic components due to electrostatic discharge		AH54.00-P-0001-01A
Notice	Notes on carrying out repair work in the vehicle interior		AH68.00-D-0001-01KOS
Notice	Notes on retrofitting electrical/ optical lines		AH82.00-P-0000-01A
22	Remove		
1.1	Remove driver seat.	Model 907	
		with code ZU8 (National version for USA)	
		except code SR8 (Swivel base for driver' seat)	
₩ĨAR			AR91.10-D-1000TS
1.2	Remove turn plate with mounted driver's seat.	Model 907	
		with code SR8 (Swivel base for driver' seat)	
		with code ZU8 (National version for USA)	
₩ĨAR			AR91.10-D-1456TS
		i Do not separate driver's seat from turn plate.	
2	Remove seat base cover from driver's seat.		

11	Remove air duct (15).		
		For this purpose, remove nuts (11).	
10	Remove air duct (12).	i	
9	Remove cover (10).		
o ₩~AR	passenger side.		AR68.30-D-0012TSR
₩ AR 8	Remove lower A-pillar trim on front		
	plate.		AR68.30-D-5021TS
7	Remove vehicle tool kit carrier		
₩ĨAR	Remove none noor coverings.		AR68.80-D-0006TSR
5	Remove seat base cover of front passenger seat. Remove front floor coverings.		
5	Remove soat base sover of front	seat from turn plate.	
₩ĨAR		i Do not disconnect front passenger	AR91.10-D-1456TS
		with code ZU8 (National version for USA)	
Τ. Ζ	front passenger seat.	with code SR9 (Swivel base for co-driver' seat)	
₩ AR 4.2	Remove turn plate with installed	Model 907	AR91.10-D-1000TS
		except code SR9 (Swivel base for co-driver' seat)	
		with code ZU8 (National version for USA)	
4.1	Remove front passenger seat.	Model 907	
		↓ unclip control units. i Do not disconnect plugs of control units.	
		If control units are installed in control unit holder (51),	
		The number of control units varies depending on the vehicle equipment.	
		Position control unit holder (51) so that ground points are accessible.	
3	Remove control unit holder (51).	If control unit holder (51) is installed. i To do so, remove nut (52).	

10			1
12	Remove cable duct (17).	i To do so, remove nuts (16).	
13	Remove battery cover (19).	i To do so, remove screws (18).	
14	Release cover (20).	i Release cover (20) using a suitable screwdriver (arrows). Release cover (20) until wiring harness can be routed.	
Х	Install		
15	Install cover (20).		
16	Install battery cover (19).	i To do so, tighten the screws (18).	
17	Install cable duct (17).	i To do so, attach nuts (16). Nm M6	BA00.10-Z-1002-01KOA
18	Install air duct (15).		
19	Install air duct (12).	i To do this, attach nuts (11). Mm M6	BA00.10-Z-1002-01KOA
20	Install cover (10).		
21	Install vehicle tool kit carrier plate.		
₩AR			AR68.30-D-5021TS
22 ⊯≆ar	Install front floor coverings.		AR68.80-D-0006TSR
23	Install lower A-pillar trim on front passenger side.		AR68.30-D-0012TSR
₩ AR 24	Attach control unit holder (51).	If control unit holder (51) is	AR00.30-D-001210R
24		 installed. Do not kink subharness during installation of control unit holder (51) and ensure that it is routed free of chafing. This prevents any damage. i To do so, attach nut (52). The number of control units varies depending on the vehicle equipment. Mm M6 If control units are installed in control unit holder (51), ↓ 	BA00.10-Z-1002-01KOA
25	Install seat base cover of driver's seat.	clip in control units.	

26.1	Install driver seat.	Model 907	
		with code ZU8 (National version for USA)	
		except code SR8 (Swivel base for driver' seat)	
₩ĨAR			AR91.10-D-1000TS
26.2	Install turn plate with driver's seat attached.	Model 907	
		with code SR8 (Swivel base for driver' seat)	
		with code ZU8 (National version for USA)	
₩ĨAR			AR91.10-D-1456TS
27	Install seat base cover of front passenger seat.		
28.1	Install front passenger seat.	Model 907	
		with code ZU8 (National version for USA)	
		except code SR9 (Swivel base for co-driver' seat)	
₩ĨAR			AR91.10-D-1000TS
28.2	Install turn plate with front passenger seat attached.	Model 907	
		with code SR9 (Swivel base for co-driver' seat)	
		with code ZU8 (National version for USA)	
₩AR			AR91.10-D-1456TS

$\ensuremath{\mathbb{N}}\xspace{\ensuremath{\mathbb{N}}}\xspace{\ensuremath{\mathbb{N}}}$ Headless screws/bolts: screws/bolts and nuts, coarse-pitch thread

Number	Designation			8.8	10.9
BA00.10-Z-1002-01KOA	M6	Galvanized	Nm	9	13
		Phosphated I	Nm	9	12

Nm Headless screws/bolts: screws/bolts and nuts, coarse-pitch thread

Number	Designation		12.9
BA00.10-Z-1002-01KOA	M6	Galvanized Nm	16
		Phosphated Nm	14

SM72.16-D-0008-04SG	Retrofit reinforcement for lock striker in C-pillar (code: VS3SCHIEBT, acc. no.: 72	
	951 62)	

Model 907.6/7 with code ZU8 (National version for USA)

1


Remove reinforcement (38) from C-pillar new part.

i

To do so, bend reinforcement (38) slightly in upper area (arrow). This makes removal easier.


i

The new C-pillar part is not required and should be disposed of properly.




D72.16-A078-82

2 Install reinforcement (38) on C-pillar (40).



D72.16-A071-76



D72.16-A080-75


Install lock striker (41). **i**

3

Tighten screws slightly by hand. Screws are tightened when adjusting sliding door.

SM72.16-D-0008-03SG	Fabricate wiring harness for sliding door (code: VS3SCHIEBT, acc. no.: 72 951 62)	
Notice	Information on preventing damage to electronic components due to electrostatic discharge	AH54.00-P-0001-01A
Notice	Notes on carrying out repair work in the vehicle interior	AH68.00-D-0001-01KOS
Notice	Notes on retrofitting electrical/ optical lines	AH82.00-P-0000-01A
₩ PE	Wiring diagram for sliding door	PE72.16-D-2001LAA


Model 907.6/7 with code ZU8 (National version for USA)



Wiring harness repair kit, basic

i

The following specified line colors for the electric lines correspond to the series production configuration and they can be replaced, if necessary, with similar line colors. Please ensure that electrical lines can be correctly assigned in accordance with slot assignment.



```
D72.16-A036-79
```

1	Prepare electric line "YE/GN". i X100/1 to RBA1 Line color "YE/GN" Length approx. 410 cm Cross section 0.5 mm ²		i X100/1 to Z21/17 Line color "BU/BN" Length approx. 232 cm Cross section 0.75 mm ²
2	Prepare electric line "BN". i X100/1 to W105/1 Line color "BN" Length approx. 255 cm Cross section 0.5 mm ²	5	Crimp contact socket (2) onto electric line "YE/GN". Use basic wiring harness repair kit. A 013 545 76 26 Contact socket
3	Prepare electric line "BU/BK". i X100/1 to Z21/16 Line color "BU/BK" Length approx. 232 cm Cross section 0.75 mm ²	6	Crimp cable lug (3) onto electric line "BN". i 3 Use basic wiring harness repair kit. i A 001 982 57 02 Cable lug
4	Prepare electric line "BU/BN".	7	Crimp contact sockets (4) on one side onto electric lines "YE/GN", "BN", "BU/ BK", "BN/BN". <u>i</u> <u>y</u> Use basic wiring harness repair kit.

i A 009 545 81 26 Contact socket A 001 545 78 80 Seal

8

Attach note in online vehicle data card under field organization texts to KG72. If line colors of prepared wiring harness (1) deviate from series production configuration.

i

Note:

Line colors of retrofitted wiring harness for sliding door deviate from series production configuration.

SM72.16-D-0008-02SGB	Retrofit wiring harness for sliding door (code: VS3SCHIEBT, acc. no.: 72 951 62)	
Notice	Information on preventing damage to electronic components due to electrostatic discharge	AH54.00-P-0001-01A
Notice	Notes on carrying out repair work in the vehicle interior	AH68.00-D-0001-01KOS
₩S	000 588 00 84 00 Heat gun	WS54.00-P-0049B
₩ĨAR	Repairing wiring harness using solder connectors	AR00.19-P-0100-09A
j≆ PE	Wiring diagram for sliding door	PE72.16-D-2001LAA

Model 907.6/7


with code EL9 (Two-way loudspeaker system in front and rear) with code ZU8 (National version for USA)

Mm Headless screws/bolts: screws/bolts and nuts, coarse-pitch thread


Number	Designation			8.8	10.9
BA00.10-Z-1002-01KOA	M6	Galvanized	Nm	9	13
		Phosphated	Nm	9	12

Nm Headless screws/bolts: screws/bolts and nuts, coarse-pitch thread


Number	Designation			12.9
BA00.10-Z-1002-01KOA	M6	Galvanized	Nm	16
		Phosphated	Nm	14



Adapter




Wiring harness repair kit, basic



Reflector

(\$)

Do not kink any electric lines and ensure that they are routed without any chafing. This prevents any damage.



D72.16-A060-78

Route electrical wiring harness (1)

i

The following specified line colors for the electric lines correspond to the series production configuration.

- 1 Route electric lines "YE/GN", "BN", "BU/ BK", as shown.
- 2 Join electric lines "YE/GN", "BN", "BU/ BK", "BU/BN" and wrap, section-bysection, with suitable insulation tape.


i

The electrical wiring harness (1) is made up of the electric lines "YE/GN", "BN", "BU/BK", "BU/BN".

Make sure that the junctions of the electric lines "YE/GN", "BN", "BU/BK", "BU/BN" remain free at the connection end.

3

Loosely fasten electrical wiring harness (1) in sections at factory-installed electrical wiring harness or at a suitable position using cable ties. Electrical wiring harness (1) to end sleeves



D72.16-A038-75

- Disconnect control circuit 1 central locking end sleeve (Z21/16) from electrical wiring harness (5).

 Electric line "BU/BK".
- 5 Connect electric line "BU/BK" of electrical wiring harness (5) and electric line "BU/BK" of electrical wiring harness (1) to new end sleeve (6).

i

To do so, use heat gun with \Im reflector or \Im adapter.

S Use basic wiring harness repair kit.

Disconnect control circuit 1 central locking end sleeve (Z21/17) from electrical wiring harness (5).



6

7

Electric line "BU/BN".

Connect electric line "BU/BN" of electrical wiring harness (5) and electric line "BU/BN" of electrical wiring harness (1) to new end sleeve (6).


i

To do so, use heat gun with \Im reflector or \Im adapter.


S Use basic wiring harness repair kit.

Electrical wiring harness (1) to signal acquisition and actuation module (SAM) control unit

8 Release and disconnect electrical connector (RBA1) from SAM (N10).



D72.16-A039-76



D72.16-A040-78

Disassemble electrical connector (RBA1). i

To do so, release plug housing (arrows A), guide out plugs (7, 8) and disconnect from each other.

10 Install electric line "YE/GN" of electrical wiring harness (1) into contact cavity 42 of plug (8).

11

i

To do so, connect plugs (7, 8) and guide into plug housing, then lock.

Assemble electrical connector (RBA1).


12 Use cable ties to fasten electric line "YE/GN" directly behind plug housing of electrical connector (RBA1) to factoryinstalled electrical wiring harness.

9

- 13 Strap down extended length of electric line "YE/GN" at suitable point.
- 14 Connect electrical connector (RBA1) to SAM control unit (N10).



D72.16-A039-76



D72.16-A061-79

Electrical wiring harness (1) to "Right sliding door electrical connector 1 (B-pillar) (X100/11x1)" or "Right

sliding door electrical connector 3 (B-pillar) (X100/11x3)" (plug (9))


15 Remove contact sockets (10) from contact cavities 1, 2, 3, 4, 7, 8 of plug (9).
i
Ear this purpose Of luse basis wiring

For this purpose, **S** use basic wiring harness repair kit.

- 16 Use fabric tape to individually insulate removed contact sockets (10).
- 17 Strap down removed contact sockets (10) at suitable point using cable tie.
- 19 Connect plug (9) to plug (11).

18

Install contact sockets (4) in plug (9). i Contact cavity 1: Electric line "YE/GN" Contact cavity 2: Electric line "BN" Contact cavity 3: Electric line BU/BN Contact cavity 4: Electric line "BU/BK" Contact cavity 5: Electric line "VT/YE" Contact cavity 6: Electric line "VT/BK"




D72.16-A062-82

20 Remove plug connector (51) from closing assist motor electrical wiring harness (8).


For this purpose, **S** use basic wiring harness repair kit.

- 21 Install blind plugs (9) into plug connector (51).
- 22 Reinstall plug connector (51) on factoryinstalled electrical wiring harness.




D72.16-A082-82

Electrical wiring harness (1) to ground connection





- 23 Remove nut of driver seat base ground point 1 (W105/1).
- 24 Connect cable lug (3) of electrical wiring harness (1) to driver seat base ground point 1 (W105/1).
- 25 Attach nut of driver seat base ground point 1 (W105/1) Nm.



Tighten electrical wiring harness (1)

26 Tighten loosely attached cable ties on complete electrical wiring harness (1). If necessary,


D72.16-A060-78

Strap down extended length of electrical wiring harness (1) at a suitable point.

SM72.16-D-0008-01SG	Convert sliding door (code: VS3SCHIEBT, acc. no.: 72	
	951 62)	

Model 907.6/7

with code EL9 (Two-way loudspeaker system in front and rear) with code ZU8 (National version for USA) with electric actuation of right sliding door




Clip remover

Repair materials

Number	Designation	Order number
BR00.45-Z-1025-04A	Cleaner	A 005 989 19 71

Refit electrical wiring harness

Shown on model 907.7 with code EL9 (2-way speaker system, front and rear)



D72.16-A049-76


1

Remove electrical wiring harness (28).

To do so, unclip electrical wiring harness (28) from sliding door (23).

The number of fastenings can vary here, depending on the equipment installed.

i The electrical wiring harness (28) is no longer required.




Shown on model 907.7 with code EL9 (2-way speaker system, front and rear)

2 Install new electrical wiring harness (29) as shown.

i Order electrical wiring harness (29) in accordance with parts catalog DG 82.607.	i Continue in the higher-level service document.


Refit cables



Route cable (31) through sliding door (23) to door handle (30).
 Handle cables carefully and do not kink them.
 Damage may occur otherwise.

i A 910 760 16 00

Install cable (31) in door handle (30).




4

D72.16-A056-79

- 5 Open cable (33). i A 910 760 15 00
- 6 Install cable (33) in bearing bracket (34).
- 7 Install cable (31) and cable (32) in cable (33).
- Close cable (33) and clip into sliding door (23). i Continue in the higher-level service document.

.

8



D72.16-A052-75


Modify sliding door detachable parts

 Remove antientrapment strip (21) from trim (22).
 I
 To do so, remove anti-entrapment strip (21) using S clip remover then remove adhesive tape.

i


The anti-entrapment strip (21) is no longer required.

- 10 Install trim (22) on sliding door (23). i To do so, install expansion rivet (24).
- 11 Install trim (25) at sliding door (23).



D72.16-A053-73

- 12 Clean contact surface of stop plug (26).
- 13 Install stop plug (26) into opening of sliding door (23). <u>i</u> A 110 987 05 44



D72.16-A047-76


14 Install cover (27) at old position of switch for deactivation of electric sliding door (23). **i**A 906 998 00 50

i To do so, use screws of switch for deactivation of electric sliding door.



D72.16-A048-76

- Remove information label (35) from sliding door.
 <u>i</u>
 The information label is no longer required.
- 16 Remove adhesive residue from sliding door.



D72.16-A057-01



Work instructions

Van

Group 72 CODE: VS3SCHIEBT

> SM72.16-D-0008B 16.05.2023

Sliding door conversion (code: VS3SCHIEBT, acc. no.: 72 951 62)

Model 907.6/7 with code ZU8 (National version for USA) except code EL9 (Two-way loudspeaker system in front and rear) with electric actuation of right sliding door

SM72.16-D-0008B	Sliding door conversion (code: VS3SCHIEBT, acc. no.: 72	05.05.2023
	951 62)	


Model 907.6/7

with code ZU8 (National version for USA) except code EL9 (Two-way loudspeaker system in front and rear) with electric actuation of right sliding door

Operation no. of the operation texts or standard texts and flat rates

Category	Op. no.	Operation text	Time	Damage Code	Code
L	02 0981	Operations: Modify sliding door on vehicle with code T55 and without code EL9/V40	6.6 hrs	72 951 62	VS3SCHIEB T

Important!
On the affected vehicles, the sliding door is converted from electrical to mechanical actuation.
Replacement parts ordering:
Before ordering the required replacement parts, the special equipment code T55 (Electrical actuation for right sliding door) must be removed from the Vehicle Documentation (VeDoc). Only then can the correct replacement parts can be determined using XENTRY Parts Information.
Vehicle documentation (VeDoc):
Changes in VeDoc can only be made by users with write permission.
If no-one with change authorization is available, a ticket must be created in the "XENTRY Support and Feedback (XSF)" system for "Vehicle data/VeDoc".
Please note that the XSF ticket has to be approved by the national organization, something which involves additional processing time.
It may take a few days for the entry to be visible in VeDoc.
In the event of problems:
If problems arise while carrying out the service measure, please create a PTSS case.
To do this, use the "DTS pre-case checklist".
The most recent version is always available via the XENTRY Portal.



Shown on vehicle with automatic transmission

- 1 Stowage compartment
- 2 Switches
- 4 Cover

3 Connector




D72.16-A044-72

Shown on vehicle with code T74 (Grab handle for entrance)

- 5 B-pillar paneling
- 6 Switches
- 7 Connector



D72.16-A043-76



8 Closing assist motor electrical wiring harness


D72.16-A051-78

- 9 Blind plug
- 13 Connector
- 14 Connector



D72.16-A046-82

- 36 Retaining bolt
- 37 Guide rail



D72.16-A058-80

<u>∧</u> Warning	Risk of injury caused by fingers being jammed or pinched when removing, installing or aligning hoods, doors, trunk lid/rear-end door or sliding roof.	No parts of the body or limbs should be within the operating area when the components are moving.	AS00.00-Z-0011-01A
≜ Caution	Risk of injury caused by scraping or cutting body parts on sharp vehicle parts	Always wear protective gloves when working on or near sharp and non-deburred vehicle parts.	AS00.00-Z-0017-01A
		Deburr repair panels.	
Notice	Information on preventing damage to electronic components due to electrostatic discharge		AH54.00-P-0001-01A
Notice	Notes on carrying out repair work in the vehicle interior		AH68.00-D-0001-01KOS
Notice	Notes on retrofitting electrical/ optical lines		AH82.00-P-0000-01A


4	Check		
1	Check if vehicle is affected by measure.		
	Update Vehicle Documentation (VeDoc)		
2	Remove special equipment from online vehicle data card.	i Remove existing code T55 (Electrical actuation for right sliding door).	
3	Attach "Sliding door converted as per SM72.16-D-0008B note" under field organization texts to KG72.		
X	Remove		
4	Detach ground line of on-board electrical system battery.		AR54.10-D-0029TS
⊯ AR ∽			
5	Remove component parts in vehicle interior for sliding door conversion.		Page 32
6	Remove stowage compartment (1) with switch (2) for electric sliding door.		
₩ F AR		i The stowage compartment (1) and switch (2) are no longer required. Information on wiring diagram: Right stowage compartment sliding door pushbutton switch (S169/2)	AR68.10-D-1513TS
7	Strap down plug (3) of switch (2) using cable ties on factory- installed electrical wiring harness or at a suitable point.	i The plug (3) is no longer required.	
8	Remove cover(4).	i To do this, unscrew screw/bolts. Cover (4) is no longer required.	

9	Remove B-pillar trim (5) on front passenger side with switch (6) for electric sliding door.		
⊯ AR		Model 907.6/7 i The B-pillar trim (5) and switch (6) are no longer required. Information on wiring diagram: Right sliding door button (S159/8)	AR68.30-D-4706TS
10	Strap down plug (7) for switch (6) using cable ties on factory- installed electrical wiring harness or at a suitable point.	i The plug (7) is no longer required.	
11 ⊯≏AR	Remove closing assist motor with lock striker in C-pillar.	i The closing assist motor is no longer required.	AR72.16-D-0002TSR
12	Remove lower guide rail for sliding door.		
⊯ AR		Model 907.6/7 i The lower carriage is no longer required.	AR72.16-D-7816TS
13	Remove closing assist motor electrical subharness (8).	 i To do so, unclip electrical subharness (8), guide it out of C- pillar then disconnect electrical connector. i Electrical subharness (8) is no longer required. Clip remover 	452 589 01 63 00
14 ⊯ ≆ AR	Remove sliding door.	Model 907.6/7	AR72.16-D-1260TSB
15	Install blind plugs (9) into plug (13).	i A 048 545 42 28 A 000 545 78 80	
16	Connect plug (13) to plug (14).		
17	Strap down plug (14) using cable ties on factory-installed electrical wiring harness or at suitable point.	i The plug (14) is no longer required. Information on wiring diagram: Right sliding door electrical connector 2 (B-pillar) (100/11x2)	


	Modify sliding door		
18	Remove switch for deactivation of		
	electric sliding door.		
₩ AR			AR72.16-D-0003TSR
		i	
		The switch is no longer required.	
10	Demonstration for all string listing		
19	Remove motor for electric sliding door with cable.		
_			AR72.29-D-5901TS
₩ F AR			AR72.29-D-590113
		i	
		The engine and cable are no	
		longer required.	
20	Remove electric sliding door		
	control unit.		
🖛 AR			AR72.29-D-5898TS
		i	
		The control unit is no longer	
		required.	
21	Remove anti-entrapment strip for		
	electric sliding door.		
₩ĨAR	5		AR72.29-D-5890TS
22	Remove center carriage for sliding		
22	door.		
		Model 907.6/7	AR72.16-D-2230TSB
₩ AR	Demonstration in the set for the set of a		
23	Remove the lock for the sliding		
	door.	Model 907.6/7	AR72.16-D-4035TSB
₩ AR			AR72.10-D-405515B
24	Install new sliding door lock.		
🖙 A R		Model 907.6/7	AR72.16-D-4035TS
		i	
		Install outside door handle cable	
		only. Do not attach remaining	
		cables.	
25	Retrofit electrical wiring harness in		Page 12
	sliding door.		
26	Remove door handle.		
⊯≊AR			AR72.16-D-6601TS
		i	
		Only remove door handle far	
		enough to gain access to cables.	
27	Modify cables in sliding door.		Page 12
			1 490 12
		i Operation stops 2 to 0 of document	
		Operation steps 3 to 9 of document reference.	
00			D 40
28	Modify sliding door detachable		Page 12
	parts.		
		i	
		Operation steps 10 to 23 of the	
		document reference.	

29	Install new center sliding carriage		
20	of sliding door.		
₩ĨAR		Model 907.6/7	AR72.16-D-2230TS
	Retrofit wiring harness in vehicle interior		
30	Fabricate wiring harness for sliding door.		
₽E	Wiring diagram for sliding door		PE72.16-D-2001LAA
		S Wiring harness repair kit, basic	Page 27 000 589 13 99 00
31	Retrofit wiring harness for sliding door.		
₩₹₩S	000 588 00 84 00 Heat gun		WS54.00-P-0049B
₩ ₽ AR	Repairing wiring harness using solder connectors		AR00.19-P-0100-09A
₩PE	Wiring diagram for sliding door		PE72.16-D-2001LAA
			Page 20
		S Reflector	220 589 01 99 41
		S Adapter	220 589 01 99 42
		S Wiring harness repair kit, basic	000 589 13 99 00
X	Install		
32	Attach new retaining bolt (36) to new lower guide rail (37).	i 20 Nm	
33	Install new lower sliding door carriage.		
₩ĨAR		Model 907.6/7	AR72.16-D-7844TS
34	Install new lower guide rail (37).		
⊯FAR			AR72.16-D-7816TS
35	Retrofit reinforcement for lock striker in C-pillar.		Page 30
36	Install sliding door.		
₩ĨAR		Model 907.6/7	AR72.16-D-1260TS
37	Adjust sliding door.		AR72.16-D-1023TS
₩ AR			AR72.10-D-102313
38	Install new B-pillar trim on front passenger side.	Madel 007 6/7	
₩ AR		Model 907.6/7	AR68.30-D-4706TS
39	Install new lower center stowage compartment on instrument panel.		
₩ AR			AR68.10-D-1513TS
40	Install removed component parts in vehicle interior for sliding door conversion.		Page 32
41	Connect ground line of on-board electrical system battery.		
₩ĨAR			AR54.10-D-0029TS


	SCN coding		
42 ₩ ≈ A D	Connect diagnostic system.		AD00.00-D-2000-06TS
₩ AD		i It is absolutely essential to precisely follow the operation steps as described in the vehicle diagnosis system.	
43	Connect charging equipment.		
i≫ AR		During the entire work procedure a sufficiently large voltage supply must be provided for the vehicle's on-board electrical system.	AR54.10-D-1127TS
		Otherwise any undervoltage that occurs may damage the control units.	
		 i Follow the operating instructions for the charger. i Use the charger to ensure that an 	
		adequate power supply (min. 12.5 V) is provided for the on- board electrical system battery.	
44	Perform SCN coding on signal acquisition and actuation module (SAM) control unit.		
₩ A R		i Under the "Control unit adaptations" menu item, follow the instructions for "SCN coding".	AR54.21-D-0015TS
45	Remove charger from vehicle.		
₩ AR			AR54.10-D-1127TS
4	Check		
46	Check sliding door for correct opening and closing.	i See Operator's Manual.	
47	Perform key function test.	i See Operator's Manual.	




Adapter



Reflector



Wiring harness repair kit, basic



Clip remover

Parts ordering note


Part no.	Designation	Quantity
A 907 540 8965 07	Electrical wiring harness for manual sliding door for vehicles WITHOUT EL9	1
A 906 630 33 00	C-pillar	1
A 910 763 01 00	Sliding base in center	1
N 000000 001152	Screw	2
A 906 720 02 04	Lock striker	1
A 000 984 31 29	Screw	2
A 910 730 39 00	Door lock (bottom)	1
A 910 998 00 50 9051	Cover Plug	n.B.
A 907 730 42 00	Cable	1
A 910 760 15 00	Cable	1
A 910 760 16 00	Cable	1
A 000 995 51 14	Line fastener	5
A 907 820 38 00	Sliding base bottom	1
N 000000 000455	Screw	2
A 910 683 18 00	Stowage tray	1
A 906 691 01 33 9051	Сар	1
A 907 631 02 00	Bracket	1
A 907 690 36 00 9051	Right sliding door B-pillar trim, grab handle	1
A 906 692 12 22	Cover (on vehicle with code V36 Roof lining)	2
A 906 692 07 22 9051	Cover	1
A 910 998 02 50 9051	Cover plug	n. B.
A 906 686 34 07 9E80	Cover plug	1
A 110 987 05 44	Plug	1
A 906 998 0050	Cover Plug	1
	Parts for electrical wiring harness:	
	Electric lines (available on free market, observe specifications)	4
A 013 545 76 26	Female contact	1
A 001 982 57 02	Cable lug (ground connection)	1
A 001 545 59 80	Blanking Plug	4
A 009 545 81 26	Female contact	4
A 000 545 71 80	Seal	4
A 000 995 25 94	Cable tie	n. B.
A 007 989 28 85	Fabric tape	n. B.

Part Number	Description	Qty
A9078213000	Contact Strip/Switch	1
N00000000455	Tapping screw; Contact Switch mount; 4,2X19	2
A0009906425	Clip nut for tapping screw	2
A9078213100	Contact Plate	1
A0009903111	Pan Head Screw; Contact Plate mount; 5X14	2

VS3SCHIEBT, acc. no.: 72 951 62)		
-------------------------------------	--	--

Model 907.6/7

with code ZU8 (National version for USA) except code EL9 (Two-way loudspeaker system in front and rear) with electric actuation of right sliding door



Clip remover

Repair materials


and rear)

Number	Designation	Order number
BR00.45-Z-1025-04A	Cleaner	A 005 989 19 71

Refit electrical wiring harness

Shown on model 907.7 with code

EL9 (2-way speaker system, front




D72.16-A049-76

1 Remove electrical wiring harness (28).

To do so, unclip electrical wiring harness (28) from sliding door (23). S

The number of fastenings can vary here, depending on the equipment installed.

i The electrical wiring harness (28) is no longer required.



Shown on model 907.7 with code EL9 (2-way speaker system, front and rear)


2 Install new electrical wiring harness (29) as shown.

i	
Order electrical wiring harness (29) in accordance with parts catalog DG 82.607.	

i

Continue in the higher-level service document.

Refit cables




D72.16-A054-79




5 Route cable (32) into sliding door (23).

A 907 760 37 00



D72.16-A055-76



```
D72.16-A056-79
```

6 Open cable (33). i A 910 760 15 00

9


- - - - - - - - -

Close cable (33) and clip into sliding door (23).

i
Continue in the higher-level service document.


- 7 Install cable (33) in bearing bracket (34).
- 8 Install cable (31) and cable (32) in cable (33).
- Modify sliding door detachable parts
 - 10 Remove antientrapment strip (21) from trim (22).
 i To do so, remove anti-entrapment strip (21) using S clip remover then remove adhesive tape.

i The anti-entrapment strip (21) is no longer required.



D72.16-A052-75

- 11 Clean contact surface of stop plug (26).
- 12 Install stop plug (26) into opening of sliding door (23). **i** A 110 987 05 44



D72.16-A047-76



D72.16-A048-76

Install cover (27) at old position of switch for deactivation of electric sliding door (23). i


A 907 766 00 97

i

13


To do so, use screws of switch for deactivation of electric sliding door.

- Remove information label (35) from sliding door (23).
 The information label is no longer required.
- 15 Remove adhesive residue from sliding door (23).




D72.16-A057-01

- 16 Attach trim (22) to sliding door (23).
 i
 To do so, install 2 expansion rivets (24) to fix trim (22) in place.
- 17 Drill holes (arrows) with Ø 5 mm on trim (22). **i**The holes (arrows) must line up with those in the sliding door (23).
- 18 Remove trim (22). i To do this, remove expansion rivets (24).
- 19 Remove drilling chips.



D72.16-A076-76


20 Attach spring lock nuts (50). A0009906425




D72.16-A075-76

21 Install trim (22) on sliding door (23).
i
To do so, install expansion rivet (24).

i Trim (25) is no longer required.



D72.16-A053-73



22 Connect contact switch (48) to plug connector (49) of new electrical wiring harness (29). **i** To do so, turn in screws (47) N00000000455

23 Install contact switch (48). A9078213000

SM72.16-D-0008-02SG	Retrofit wiring harness for sliding door (code: VS3SCHIEBT, acc. no.: 72 951 62)	
Notice	Information on preventing damage to electronic components due to electrostatic discharge	AH54.00-P-0001-01A
Notice	Notes on carrying out repair work in the vehicle interior	AH68.00-D-0001-01KOS
₩S	000 588 00 84 00 Heat gun	WS54.00-P-0049B
₩ĨAR	Repairing wiring harness using solder connectors	AR00.19-P-0100-09A
₽E	Wiring diagram for sliding door	PE72.16-D-2001LAA

Model 907.6/7


with code ZU8 (National version for USA) except code EL9 (Two-way loudspeaker system in front and rear)

Nm Headless screws/bolts: screws/bolts and nuts, coarse-pitch thread


Number	Designation			8.8	10.9
BA00.10-Z-1002-01KOA	M6	Galvanized N	١m	9	13
		Phosphated N	١m	9	12

Nm Headless screws/bolts: screws/bolts and nuts, coarse-pitch thread


Number	Designation			12.9
BA00.10-Z-1002-01KOA	M6	Galvanized	Nm	16
		Phosphated	Nm	14



Adapter



Wiring harness repair kit, basic




Reflector

٤!)

Do not kink any electric lines and ensure that they are routed without any chafing.

This prevents any damage.



D72.16-A037-78

Route electrical wiring harness (1)

i

The following specified line colors for the electric lines correspond to the series production configuration.

- 1 Route electric lines "YE/GN", "BN", "BU/ BK", as shown.
- 2 Join electric lines "YE/GN", "BN", "BU/ BK", "BU/BN" and wrap, section-bysection, with suitable insulation tape.

i


The electrical wiring harness (1) is made up of the electric lines "YE/GN", "BN", "BU/BK", "BU/BN".

Make sure that the junctions of the electric lines "YE/GN", "BN", "BU/BK", "BU/BN" remain free at the connection end.

3

Loosely fasten electrical wiring harness (1) in sections at factory-installed electrical wiring harness or at a suitable position using cable ties.

Electrical wiring harness (1) to end sleeves



D72.16-A038-75

4 Disconnect control circuit 1 central locking end sleeve (Z21/16) from electrical wiring harness (5).

Electric line "BU/BK".

Connect electric line "BU/BK" of electrical wiring harness (5) and electric line "BU/BK" of electrical wiring harness (1) to new end sleeve (6).

i

5

To do so, use heat gun with \Im reflector or \Im adapter.

S Use basic wiring harness repair kit.

Disconnect control circuit 1 central locking end sleeve (Z21/17) from electrical wiring harness (5).

i

6

7

Electric line "BU/BN".

Connect electric line "BU/BN" of electrical wiring harness (5) and electric line "BU/BN" of electrical wiring harness (1) to new end sleeve (6).

i

To do so, use heat gun with \Im reflector or \Im adapter.


S Use basic wiring harness repair kit.

Electrical wiring harness (1) to signal acquisition and actuation module (SAM) control unit


8 Release and disconnect electrical connector (RBA1) from SAM (N10).



D72.16-A039-76







D72.16-A040-78

Disassemble electrical connector (RBA1).

i

9

To do so, release plug housing (arrows A), guide out plugs (7, 8) and disconnect from each other.

10 Install electric line "YE/GN" of electrical wiring harness (1) into contact cavity 42 of plug (8). 11

Assemble electrical connector (RBA1). **i** To do so, connect plugs (7, 8) and guide

To do so, connect plugs (7, 8) and guide into plug housing, then lock.


12 Use cable ties to fasten electric line "YE/GN" directly behind plug housing of electrical connector (RBA1) to factoryinstalled electrical wiring harness.

- 13 Strap down extended length of electric line "YE/GN" at suitable point.
- 14 Connect electrical connector (RBA1) to SAM control unit (N10).



D72.16-A039-76

Electrical wiring harness (1) to "Right sliding door contact plate 1 electrical connector (X100/1)" (plug (9))



D72.16-A041-75

15 Release plug (9) (arrow B). i A 048 545 42 28 Plug


16 Install contact sockets (4) in plug (9).

i

Contact cavity 1: Electric line **"YE/GN"** Contact cavity 3: Electrical line **"BN"** Contact cavity 4: Electrical line **BU/BN** Contact cavity 5: Electrical line **"BU/BK"**


17 Lock plug (9).

Electrical wiring harness (1) to ground connection



D72.16-A042-11

- 18 Remove nut of driver seat base ground point 1 (W105/1).
- 19 Connect cable lug (3) of electrical wiring harness (1) to driver seat base ground point 1 (W105/1).
- 20 Attach nut of driver seat base ground point 1 (W105/1) Nm.




D72.16-A037-78

Tighten electrical wiring harness (1)

21 Tighten loosely attached cable ties on complete electrical wiring harness (1). If necessary,

↓ Strap down extended length of electrical wiring harness (1) at a suitable point. 22


Install contact plate (38) A9078213100 **i** To do so, connect plug (9) and screw in screws. A0009903111



D72.16-A059-75

SM72.16-D-0008-03SG	Fabricate wiring harness for sliding door (code: VS3SCHIEBT, acc. no.: 72 951 62)	
Notice	Information on preventing damage to electronic components due to electrostatic discharge	AH54.00-P-0001-01A
Notice	Notes on carrying out repair work in the vehicle interior	AH68.00-D-0001-01KOS
Notice	Notes on retrofitting electrical/ optical lines	AH82.00-P-0000-01A
₽₽	Wiring diagram for sliding door	PE72.16-D-2001LAA


Model 907.6/7 with code ZU8 (National version for USA)



Wiring harness repair kit, basic

i

The following specified line colors for the electric lines correspond to the series production configuration and they can be replaced, if necessary, with similar line colors. Please ensure that electrical lines can be correctly assigned in accordance with slot assignment.



```
D72.16-A036-79
```

1	Prepare electric line "YE/GN". i X100/1 to RBA1 Line color "YE/GN" Length approx. 410 cm Cross section 0.5 mm ²		i X100/1 to Z21/17 Line color "BU/BN" Length approx. 232 cm Cross section 0.75 mm ²
2	Prepare electric line "BN". i X100/1 to W105/1 Line color "BN" Length approx. 255 cm Cross section 0.5 mm ²	5	Crimp contact socket (2) onto electric line "YE/GN". Use basic wiring harness repair kit. A 013 545 76 26 Contact socket
3	Prepare electric line "BU/BK". i X100/1 to Z21/16 Line color "BU/BK" Length approx. 232 cm Cross section 0.75 mm ²	6	Crimp cable lug (3) onto electric line "BN". i 3 Use basic wiring harness repair kit. i A 001 982 57 02 Cable lug
4	Prepare electric line "BU/BN".	7	Crimp contact sockets (4) on one side onto electric lines "YE/GN", "BN", "BU/ BK", "BN/BN". i S' Use basic wiring harness repair kit.

i A 009 545 81 26 Contact socket A 001 545 78 80 Seal

8

Attach note in online vehicle data card under field organization texts to KG72. If line colors of prepared wiring harness (1) deviate from series production configuration.

i

Note:

Line colors of retrofitted wiring harness for sliding door deviate from series production configuration.

SM72.16-D-0008-04SG	Retrofit reinforcement for lock striker in C-pillar (code: VS3SCHIEBT, acc. no.: 72	
	951 62)	

Model 907.6/7 with code ZU8 (National version for USA)

1


Remove reinforcement (38) from C-pillar new part.

i

To do so, bend reinforcement (38) slightly in upper area (arrow). This makes removal easier.


i

The new C-pillar part is not required and should be disposed of properly.




D72.16-A078-82

2 Install reinforcement (38) on C-pillar (40).



D72.16-A071-76



D72.16-A080-75


3

Install lock striker (41). i Tighten screws slightly by hand. Screws are tightened when adjusting sliding door.

SM72.16-D-0009SG	Prepare vehicle interior at front for sliding door conversion	18.07.2022
	(code: VS3SCHIEBT, acc. no.: 72 951 62)	

Model 907

with code ZU8 (National version for USA)



51 Control unit bracket 52 Nut

D54.21-A026-09

Shown on model 907.7 without S23 (Front passenger bench seat)


- 10 Cover
- 11 Nuts
- 12 Air duct



D31.19-1216-12

Shown on model 907.7 without S23 (Front passenger bench seat)

- 15 Air duct
- 16 Nuts
- 17 Cable duct
- 18 Bolts
- 19 Battery cover
- 20 Cover



D31.19-1217-06

<u>∧</u> Warning	Risk of injury caused by fingers being jammed or pinched when removing, installing or aligning hoods, doors, trunk lid/rear-end door or sliding roof.	No parts of the body or limbs should be within the operating area when the components are moving.	AS00.00-Z-0011-01A
<u> </u>	Risk of injury caused by scraping or cutting body parts on sharp vehicle parts	Always wear protective gloves when working on or near sharp and non-deburred vehicle parts.	AS00.00-Z-0017-01A
		Deburr repair panels.	
Notice	Information on preventing damage to electronic components due to electrostatic discharge		AH54.00-P-0001-01A
Notice	Notes on carrying out repair work in the vehicle interior		AH68.00-D-0001-01KOS
Notice	Notes on retrofitting electrical/ optical lines		AH82.00-P-0000-01A
22	Remove		
1.1	Remove driver seat.	Model 907	
		with code ZU8 (National version for USA)	
		except code SR8 (Swivel base for driver' seat)	
₩ĨAR			AR91.10-D-1000TS
1.2	Remove turn plate with mounted driver's seat.	Model 907	
		with code SR8 (Swivel base for driver' seat)	
		with code ZU8 (National version for USA)	
₩ĨAR			AR91.10-D-1456TS
		i Do not separate driver's seat from turn plate.	
2	Remove seat base cover from driver's seat.		

3	Remove control unit holder (51).	If control unit holder (51) is installed.	
		i To do so, remove nut (52).	
		Position control unit holder (51) so that ground points are accessible.	
		The number of control units varies	
		depending on the vehicle equipment.	
		If control units are installed in control unit holder (51),	
		Ļ	
		unclip control units.	
		i	
		Do not disconnect plugs of control units.	
4.1	Remove front passenger seat.	Model 907	
		with code ZU8 (National version for USA)	
		except code SR9 (Swivel base for co-driver' seat)	
			AD04 40 D 4000TC
Mar AR			AR91.10-D-1000TS
4.2	Remove turn plate with installed front passenger seat.	Model 907	
	non passenger seat.	with code SR9 (Swivel base for co-driver' seat)	
		with code ZU8 (National version for USA)	
			AR91.10-D-1456TS
⊯ AR		i	
		Do not disconnect front passenger seat from turn plate.	
5	Remove seat base cover of front passenger seat.		
6	Remove front floor coverings.		
₩FAR			AR68.80-D-0006TSR
7	Remove vehicle tool kit carrier plate.		
₩ĨAR			AR68.30-D-5021TS
8	Remove lower A-pillar trim on front passenger side.		
₩ĨAR			AR68.30-D-0012TSR
9	Remove cover (10).		
10	Remove air duct (12).	i	
		For this purpose, remove nuts (11).	
11	Remove air duct (15).		

10]
12	Remove cable duct (17).	i To do so, remove nuts (16).	
13	Remove battery cover (19).	i To do so, remove screws (18).	
14	Release cover (20).	i Release cover (20) using a suitable screwdriver (arrows). Release cover (20) until wiring harness can be routed.	
X	Install		
15	Install cover (20).		
16	Install battery cover (19).	i To do so, tighten the screws (18).	
17	Install cable duct (17).	i To do so, attach nuts (16). Nm M6	BA00.10-Z-1002-01KOA
18	Install air duct (15).		
19	Install air duct (12).	i To do this, attach nuts (11). Nm M6	BA00.10-Z-1002-01KOA
20	Install cover (10).		
21	Install vehicle tool kit carrier plate.		
₩ĨAR			AR68.30-D-5021TS
22 ⊯ ∽A R	Install front floor coverings.		AR68.80-D-0006TSR
23 F AR	Install lower A-pillar trim on front passenger side.		AR68.30-D-0012TSR
24	Attach control unit holder (51).	If control unit holder (51) is installed. () Do not kink subharness during installation of control unit holder (51) and ensure that it is routed free of chafing. This prevents any damage. I To do so, attach nut (52). The number of control units varies depending on the vehicle equipment. Nm M6 If control units are installed in control unit holder (51), ↓	BA00.10-Z-1002-01KOA
25	Install seat base cover of driver's seat.	clip in control units.	

26.1	Install driver seat.	Model 907	
		with code ZU8 (National version for USA)	
		except code SR8 (Swivel base for driver' seat)	
₩AR			AR91.10-D-1000TS
26.2	Install turn plate with driver's seat attached.	Model 907	
		with code SR8 (Swivel base for driver' seat)	
		with code ZU8 (National version for USA)	
₩AR			AR91.10-D-1456TS
27	Install seat base cover of front passenger seat.		
28.1	Install front passenger seat.	Model 907	
		with code ZU8 (National version for USA)	
		except code SR9 (Swivel base for co-driver' seat)	
₩ĨAR			AR91.10-D-1000TS
28.2	Install turn plate with front passenger seat attached.	Model 907	
		with code SR9 (Swivel base for co-driver' seat)	
		with code ZU8 (National version for USA)	
₩AR			AR91.10-D-1456TS

$\ensuremath{\mathbb{N}}\xspace{\ensuremath{\mathbb{N}}}\xspace{\ensuremath{\mathbb{N}}}$ Headless screws/bolts: screws/bolts and nuts, coarse-pitch thread

Number	Designation			8.8	10.9
BA00.10-Z-1002-01KOA	M6	Galvanized	Nm	9	13
		Phosphated I	Nm	9	12

Nm Headless screws/bolts: screws/bolts and nuts, coarse-pitch thread

Number	Designation		12.9
BA00.10-Z-1002-01KOA	M6	Galvanized Nm	16
		Phosphated Nm	14



Work instructions

Van

Group 72 CODE: VS3SCHIEBT

> SM72.16-D-0008C 16.05.2023

Sliding door conversion (code: VS3SCHIEBT, acc. no.: 72 951 62)

Model 907.6/7 with code EL9 (Two-way loudspeaker system in front and rear) with code ZU8 (National version for USA) with electric closing assist of right sliding door

SM72.16-D-0008C	Sliding door conversion (code: VS3SCHIEBT, acc. no.: 72	05.05.2023
	951 62)	

Model 907.6/7

with code EL9 (Two-way loudspeaker system in front and rear) with code ZU8 (National version for USA) with electric closing assist of right sliding door


Operation no. of the operation texts or standard texts and flat rates

Category Op. n	no. Operation text	Time	Damage Code	Code
L 02 09	982 Operations: Mod code T50/EL9/V2	 4.1hr	72 951 62	VS3SCHIEB T

Important!
On affected vehicles, the sliding door closing assist is removed.
Replacement parts ordering:
Before ordering the required replacement parts, the special equipment code T50 (Electrical closing assist for right sliding door) must be removed from the Vehicle Documentation (VeDoc). Only then can the correct replacement parts can be determined using XENTRY Parts Information.
Vehicle documentation (VeDoc):
Changes in VeDoc can only be made by users with write permission.
If no-one with change authorization is available, a ticket must be created in the "XENTRY Support and Feedback (XSF)" system for "Vehicle data/VeDoc".
Please note that the XSF ticket has to be approved by the national organization, something which involves addition processing time.
It may take a few days for the entry to be visible in VeDoc.
In the event of problems:
If problems arise while carrying out the service measure, please create a PTSS case.

To do this, use the "DTS pre-case checklist".

The most recent version is always available via the XENTRY Portal.



D72.16-A051-78


8 Closing assist motor electrical wiring harness

Warning	Risk of injury caused by fingers being jammed or pinched when removing, installing or aligning hoods, doors, trunk lid/rear-end door or sliding roof.	No parts of the body or limbs should be within the operating area when the components are moving.	AS00.00-Z-0011-01A
<u> </u>	Risk of injury caused by scraping or cutting body parts on sharp vehicle parts	Always wear protective gloves when working on or near sharp and non-deburred vehicle parts. Deburr repair panels.	AS00.00-Z-0017-01A
Notice	Information on preventing damage to electronic components due to electrostatic discharge		AH54.00-P-0001-01A
Notice	Notes on carrying out repair work in the vehicle interior		AH68.00-D-0001-01KOS
Notice	Notes on retrofitting electrical/ optical lines		AH82.00-P-0000-01A
4	Check		
1	Check if vehicle is affected by measure.		
	Update Vehicle Documentation (VeDoc)		
2	Remove special equipment from online vehicle data card.	i Remove existing code T50 (Electric closing assist for right sliding door).	

			1
3	Attach "Sliding door converted as		
	per SM72.16-D-0008C note" under field organization texts to		
	KG72.		
23	Remove		
4	Detach ground line of on-board		
	electrical system battery.		
₩ĨAR			AR54.10-D-0029TS
5	Remove component parts in		Page 23
	vehicle interior for sliding door conversion.		
6	Remove closing assist motor with lock striker in C-pillar.		
₩ĨAR			AR72.16-D-0002TSR
		i	
		The closing assist motor is no	
		longer required.	
7	Remove lower guide rail for sliding door.		
	0001.	Model 907.6/7	AR72.16-D-7816TS
AR 8	Remove closing assist motor	i	
0	electrical subharness (8).	To do so, unclip electrical	
		subharness (8), guide it out of C-	
		pillar then disconnect electrical	
		connector.	
		i	
		The electrical subharness (8) is no	
		longer required.	
		S Clip remover	452 589 01 63 00
	Modify sliding door		
9	Remove electric sliding door		
	control unit.		
₩ĨAR			AR72.29-D-5898TS
		i	
		The control unit is no longer	
		required.	
10	Retrofit electrical wiring harness in sliding door.		Page 6
	Retrofit wiring harness in vehicle interior		
11	Fabricate wiring harness for sliding door.		
₩ PE	Wiring diagram for sliding door		PE72.16-D-2001LAA
		S Wiring harness repair kit, basic	Page 18 000 589 13 99 00


			1
12	Retrofit wiring harness for sliding door.		
₩₹₩S	000 588 00 84 00 Heat gun		WS54.00-P-0049B
i≕ w S i≆ AR	Repairing wiring harness using		AR00.19-P-0100-09A
	solder connectors		
⊯ PE	Wiring diagram for sliding door		PE72.16-D-2001LAA
⊯≊ PE	Wiring diagram for loudspeakers		PE82.62-D-2102LAA
			Page 10
		S Reflector	220 589 01 99 41
		S Adapter	220 589 01 99 42
		S Wiring harness repair kit, basic	000 589 13 99 00
X	Install		
13	Retrofit reinforcement for lock striker in C-pillar.		Page 21
14	Install lower guide rail for sliding door.		
₩ĨAR		Model 907.6/7	AR72.16-D-7816TS
15	Install removed component parts in vehicle interior for sliding door conversion.		Page 23
16	Connect ground line of on-board electrical system battery.		
₩ĨAR			AR54.10-D-0029TS
	SCN coding		
17	Connect diagnostic system.		
₩ĨAD			AD00.00-D-2000-06TS
		i	
		It is absolutely essential to	
		precisely follow the operation steps as described in the vehicle	
		diagnosis system.	
18	Connect charging equipment.		
⊯≊AR			AR54.10-D-1127TS
		During the entire work procedure a	
		sufficiently large voltage supply must be provided for the vehicle's	
		on-board electrical system.	
		Otherwise any undervoltage that	
		occurs may damage the control units.	
		i	
		Follow the operating instructions for the charger.	
		i	
		Use the charger to ensure that an	
		adequate power supply (min.	
		12.5 V) is provided for the on- board electrical system battery.	
		Soard Ciccurca System Dattery.	

19	Perform SCN coding on signal acquisition and actuation module (SAM) control unit.		
₩AR			AR54.21-D-0015TS
		i Under the "Control unit adaptations" menu item, follow the instructions for "SCN coding".	
20	Remove charger from vehicle.		
₩ AR			AR54.10-D-1127TS
◄	Check		
21	Check sliding door for correct opening and closing.	i See Operator's Manual.	




Parts ordering note


Adapter



Reflector



Wiring harness repair kit, basic




Clip remover

Part no.	Designation	Quantity
A 907 540 8965 08	Electrical wiring harness for manual sliding door for vehicles with EL9	1
A 906 630 33 00	C-pillar	1
A 906 720 02 04	Lock striker	1
A 000 984 31 29	Screw	2
A 000 995 51 14	Line fastener	5
N 000000 000455	Screw	2
A 906 692 12 22	Cover (on vehicle with code V36 Roof lining)	2
A 906 692 07 22 9051	Cover	1
A 910 998 02 50 9051	Cover plug	n. B.
A 910 998 00 50 9051	Cover plug	n. B.
A 110 987 05 44	Cover plug	1
	Parts for electrical wiring harness:	
	Electric lines (available on free market, observe specifications)	4
A 013 545 76 26	Female contact	1
A 001 982 57 02	Cable lug (ground connection)	1
A 001 545 59 80	Seal	4
A 009 545 81 26	Female contact	4
A 000 545 78 80	Plug	4
A 000 995 25 94	Cable tie	n. B.

SM72.16-D-0008-01SGB	Convert sliding door (code: VS3SCHIEBT, acc. no.: 72 951 62)		
----------------------	--	--	--

Model 907.6/7


with code ZU8 (National version for USA) with electric closing assist of right sliding door



Clip remover

Refit electrical wiring harness

Shown on model 907.7 with code EL9 (2-way speaker system, front and rear)



D72.16-A049-76

1 Remove electrical wiring harness (28).


i

To do so, unclip electrical wiring harness (28) from sliding door (23). 🔗

The number of fastenings can vary here, depending on the equipment installed.

i

The electrical wiring harness (28) is no longer required.



Shown on model 907.7 with code EL9 (2-way speaker system, front and rear)


2 Install new electrical wiring harness (29) as shown.

i Order electrical wiring harness (29) in accordance with parts catalog DG 82.607.

i

Continue in the higher-level service document.

Modify sliding door detachable parts



4

5

D72.16-A079-79

3 Remove lower carriage (42) from sliding door.

i For this purpose, remove screws (43).

i


The removed lower carriage (42) is no longer required.

6


Remove cover (46).

To do this, remove screws (47).

- Release cable duct (44) (arrow) and remove from lower sliding carriage (42).
- Remove cable duct (44) with electrical wiring harness (45).



D72.16-A081-81



7 Connect contact switch (48) to plug connector (49) of new electrical wiring harness (29). **i** To do so, turn in screws (47).

8 Install contact switch (48).

SM72.16-D-0008-02SGB	Retrofit wiring harness for sliding door (code: VS3SCHIEBT, acc. no.: 72 951 62)	
Notice	Information on preventing damage to electronic components due to electrostatic discharge	AH54.00-P-0001-01A
Notice	Notes on carrying out repair work in the vehicle interior	AH68.00-D-0001-01KOS
₩S	000 588 00 84 00 Heat gun	WS54.00-P-0049B
₩AR	Repairing wiring harness using solder connectors	AR00.19-P-0100-09A
₽E	Wiring diagram for sliding door	PE72.16-D-2001LAA

Model 907.6/7


with code EL9 (Two-way loudspeaker system in front and rear) with code ZU8 (National version for USA)

Nm Headless screws/bolts: screws/bolts and nuts, coarse-pitch thread


Number	Designation			8.8	10.9
BA00.10-Z-1002-01KOA	M6	Galvanized	Nm	9	13
		Phosphated	Nm	9	12

Nm Headless screws/bolts: screws/bolts and nuts, coarse-pitch thread


Number	Designation			12.9
BA00.10-Z-1002-01KOA	M6	Galvanized	Nm	16
		Phosphated	Nm	14



Adapter




Wiring harness repair kit, basic



Reflector

Do not kink any electric lines and ensure that they are routed without any chafing.

This prevents any damage.



D72.16-A060-78

Route electrical wiring harness (1)

i

The following specified line colors for the electric lines correspond to the series production configuration.

- 1 Route electric lines "YE/GN", "BN", "BU/ BK", as shown.
- 2 Join electric lines "YE/GN", "BN", "BU/ BK", "BU/BN" and wrap, section-bysection, with suitable insulation tape.

i


The electrical wiring harness (1) is made up of the electric lines "YE/GN", "BN", "BU/BK", "BU/BN".

Make sure that the junctions of the electric lines "YE/GN", "BN", "BU/BK", "BU/BN" remain free at the connection end.

3

Loosely fasten electrical wiring harness (1) in sections at factory-installed electrical wiring harness or at a suitable position using cable ties.

Electrical wiring harness (1) to end sleeves



D72.16-A038-75

4 Disconnect control circuit 1 central locking end sleeve (Z21/16) from electrical wiring harness (5).

Electric line "BU/BK".

Connect electric line "BU/BK" of electrical wiring harness (5) and electric line "BU/BK" of electrical wiring harness (1) to new end sleeve (6).

i

5

To do so, use heat gun with \Im reflector or \Im adapter.

S Use basic wiring harness repair kit.

Disconnect control circuit 1 central locking end sleeve (Z21/17) from electrical wiring harness (5).

i

6

7

Electric line "BU/BN".

Connect electric line "BU/BN" of electrical wiring harness (5) and electric line "BU/BN" of electrical wiring harness (1) to new end sleeve (6).

i

To do so, use heat gun with \Im reflector or \Im adapter.


S Use basic wiring harness repair kit.


Electrical wiring harness (1) to signal acquisition and actuation module (SAM) control unit

8 Release and disconnect electrical connector (RBA1) from SAM (N10).



D72.16-A039-76





D72.16-A040-78

Disassemble electrical connector (RBA1).

i

9

To do so, release plug housing (arrows A), guide out plugs (7, 8) and disconnect from each other.

10 Install electric line "YE/GN" of electrical wiring harness (1) into contact cavity 42 of plug (8). 11

Assemble electrical connector (RBA1). **i** To do so, connect plugs (7, 8) and guide


To do so, connect plugs (7, 8) and guide into plug housing, then lock.

12 Use cable ties to fasten electric line "YE/GN" directly behind plug housing of electrical connector (RBA1) to factoryinstalled electrical wiring harness.

- 13 Strap down extended length of electric line "YE/GN" at suitable point.
- 14 Connect electrical connector (RBA1) to SAM control unit (N10).



D72.16-A039-76



D72.16-A061-79

Electrical wiring harness (1) to "Right sliding door electrical connector 1 (B-pillar) (X100/11x1)" or "Right

sliding door electrical connector 3 (B-pillar) (X100/11x3)" (plug (9))


15 Remove contact sockets (10) from contact cavities 1, 2, 3, 4, 7, 8 of plug (9).
i

For this purpose, **S** use basic wiring harness repair kit.

- 16 Use fabric tape to individually insulate removed contact sockets (10).
- 17 Strap down removed contact sockets (10) at suitable point using cable tie.
- 19 Connect plug (9) to plug (11).

18

 Install contact sockets (4) in plug (9).
 Contact cavity 1: Electric line "YE/GN" Contact cavity 2: Electric line "BN" Contact cavity 3: Electric line BU/BN Contact cavity 4: Electric line "BU/BK" Contact cavity 5: Electric line "VT/YE" Contact cavity 6: Electric line "VT/BK"




D72.16-A062-82

20 Remove plug connector (51) from closing assist motor electrical wiring harness (8).

i


For this purpose, **S** use basic wiring harness repair kit.

- 21 Install blind plugs (9) into plug connector (51).
- 22 Reinstall plug connector (51) on factoryinstalled electrical wiring harness.



D72.16-A082-82

Electrical wiring harness (1) to ground connection






- 23 Remove nut of driver seat base ground point 1 (W105/1).
- 24 Connect cable lug (3) of electrical wiring harness (1) to driver seat base ground point 1 (W105/1).

25

Attach nut of driver seat base ground point 1 (W105/1) Nm.



Tighten electrical wiring harness (1)


26 Tighten loosely attached cable ties on complete electrical wiring harness (1). If necessary,

Strap down extended length of electrical wiring harness (1) at a suitable point.

Ļ

SM72.16-D-0008-03SG	Fabricate wiring harness for sliding door (code: VS3SCHIEBT, acc. no.: 72 951 62)	
Notice	Information on preventing damage to electronic components due to electrostatic discharge	AH54.00-P-0001-01A
Notice	Notes on carrying out repair work in the vehicle interior	AH68.00-D-0001-01KOS
Notice	Notes on retrofitting electrical/ optical lines	AH82.00-P-0000-01A
₩ PE	Wiring diagram for sliding door	PE72.16-D-2001LAA


Model 907.6/7 with code ZU8 (National version for USA)



Wiring harness repair kit, basic

i

The following specified line colors for the electric lines correspond to the series production configuration and they can be replaced, if necessary, with similar line colors. Please ensure that electrical lines can be correctly assigned in accordance with slot assignment.



```
D72.16-A036-79
```

1	Prepare electric line "YE/GN". i X100/1 to RBA1 Line color "YE/GN" Length approx. 410 cm Cross section 0.5 mm ²		i X100/1 to Z21/17 Line color "BU/BN" Length approx. 232 cm Cross section 0.75 mm ²
2	Prepare electric line "BN". i X100/1 to W105/1 Line color "BN" Length approx. 255 cm Cross section 0.5 mm ²	5	Crimp contact socket (2) onto electric line "YE/GN".
3	Prepare electric line "BU/BK". i X100/1 to Z21/16 Line color "BU/BK" Length approx. 232 cm Cross section 0.75 mm ²	6	Crimp cable lug (3) onto electric line "BN". Use basic wiring harness repair kit. A 001 982 57 02 Cable lug
4	Prepare electric line "BU/BN".	7	Crimp contact sockets (4) on one side onto electric lines "YE/GN", "BN", "BU/ BK", "BN/BN". <u>i</u> Use basic wiring harness repair kit.

i A 009 545 81 26 Contact socket A 001 545 78 80 Seal

8

Attach note in online vehicle data card under field organization texts to KG72. If line colors of prepared wiring harness (1) deviate from series production configuration.

i

Note:

Line colors of retrofitted wiring harness for sliding door deviate from series production configuration.

	Retrofit reinforcement for lock striker in C-pillar (code: VS3SCHIEBT, acc. no.: 72 951 62)		
--	--	--	--

Model 907.6/7 with code ZU8 (National version for USA)

1


Remove reinforcement (38) from C-pillar new part.

i

To do so, bend reinforcement (38) slightly in upper area (arrow). This makes removal easier.


i

The new C-pillar part is not required and should be disposed of properly.



D72.16-A078-82

2 Install reinforcement (38) on C-pillar (40).



D72.16-A071-76



D72.16-A080-75


Install lock striker (41). i Tighten screws slightly by hand. Screws are tightened when adjusting sliding door.

3

SM72.16-D-0009SG Prepare vehicle interior at front for sliding door conversion		18.07.2022
	(code: VS3SCHIEBT, acc. no.: 72 951 62)	

Model 907

with code ZU8 (National version for USA)



51 Control unit bracket

52 Nut

D54.21-A026-09

Shown on model 907.7 without S23 (Front passenger bench seat)


- 10 Cover
- 11 Nuts
- 12 Air duct



D31.19-1216-12

Shown on model 907.7 without S23 (Front passenger bench seat)

- 15 Air duct
- 16 Nuts
- 17 Cable duct
- 18 Bolts
- 19 Battery cover
- 20 Cover



D31.19-1217-06

<u>∧</u> Warning	Risk of injury caused by fingers being jammed or pinched when removing, installing or aligning hoods, doors, trunk lid/rear-end door or sliding roof.	No parts of the body or limbs should be within the operating area when the components are moving.	AS00.00-Z-0011-01A
⚠ Caution	Risk of injury caused by scraping or cutting body parts on sharp vehicle parts	Always wear protective gloves when working on or near sharp and non-deburred vehicle parts.	AS00.00-Z-0017-01A
		Deburr repair panels.	
Notice	Information on preventing damage to electronic components due to electrostatic discharge		AH54.00-P-0001-01A
Notice	Notes on carrying out repair work in the vehicle interior		AH68.00-D-0001-01KOS
Notice	Notes on retrofitting electrical/ optical lines		AH82.00-P-0000-01A
X	Remove		
1.1	Remove driver seat.	Model 907	
		with code ZU8 (National version for USA)	
		except code SR8 (Swivel base for driver' seat)	
₩ĨAR			AR91.10-D-1000TS
1.2	Remove turn plate with mounted driver's seat.	Model 907	
		with code SR8 (Swivel base for driver' seat)	
		with code ZU8 (National version for USA)	
₩ĨAR			AR91.10-D-1456TS
		i Do not separate driver's seat from turn plate.	
2	Remove seat base cover from driver's seat.		

3	Remove control unit holder (51).	If control unit holder (51) is	
		installed.	
		i To do so, romovo put (52)	
		To do so, remove nut (52).	
		Position control unit holder (51) so that ground points are accessible.	
		The number of control units varies depending on the vehicle equipment.	
		If control units are installed in control unit holder (51),	
		Ļ	
		unclip control units.	
		i	
		Do not disconnect plugs of control units.	
4.1	Remove front passenger seat.	Model 907	
		with code ZU8 (National version for USA)	
		except code SR9 (Swivel base for co-driver' seat)	
₩ĨAR			AR91.10-D-1000TS
4.2	Remove turn plate with installed	Model 907	
	front passenger seat.		
		with code SR9 (Swivel base for co-driver' seat)	
		with code ZU8 (National version for USA)	
₩ĨAR			AR91.10-D-1456TS
		i	
		Do not disconnect front passenger seat from turn plate.	
5	Remove seat base cover of front passenger seat.		
6	Remove front floor coverings.		
₩ĨAR			AR68.80-D-0006TSR
7	Remove vehicle tool kit carrier		
	plate.		AR68.30-D-5021TS
₩ FAR 8	Remove lower A-pillar trim on front		
	passenger side.		
AR			AR68.30-D-0012TSR
9	Remove cover (10).		
10	Remove air duct (12).	i For this purpose, remove nuts (11).	
11	Remove air duct (15).		

12	Remove cable duct (17).	i To do oo, romovo puto (16)		
		To do so, remove nuts (16).		
13	Remove battery cover (19).	Image: Image of the sector		
14	Release cover (20).	i Release cover (20) using a suitable screwdriver (arrows). Release cover (20) until wiring		
		harness can be routed.		
X	Install			
15	Install cover (20).			
16	Install battery cover (19).	i To do so, tighten the screws (18).		
17	Install cable duct (17).	i To do so, attach nuts (16). Nm M6		
18	Install air duct (15).			
19	Install air duct (12).	i To do this, attach nuts (11).		
		Nm M6	BA00.10-Z-1002-01KOA	
20	Install cover (10).			
21 F AR	Install vehicle tool kit carrier plate.		AR68.30-D-5021TS	
22 AR	Install front floor coverings.		AR68.80-D-0006TSR	
23	Install lower A-pillar trim on front passenger side.			
₩ AR			AR68.30-D-0012TSR	
24	Attach control unit holder (51).	If control unit holder (51) is installed. Do not kink subharness during installation of control unit holder (51) and ensure that it is routed free of chafing. This prevents any damage. i To do so, attach nut (52). The number of control units varies depending on the vehicle equipment. Mm M6 If control units are installed in control unit holder (51),	BA00.10-Z-1002-01KOA	
		clip in control units.		

26.1	Install driver seat.	Model 907	
		with code ZU8 (National version for USA)	
		except code SR8 (Swivel base for driver' seat)	
₩ĨAR			AR91.10-D-1000TS
26.2	Install turn plate with driver's seat attached.	Model 907	
	สแสบายน.	with code SR8 (Swivel base for driver' seat)	
		with code ZU8 (National version for USA)	
₩ĨAR			AR91.10-D-1456TS
27	Install seat base cover of front passenger seat.		
28.1	Install front passenger seat.	Model 907	
		with code ZU8 (National version for USA)	
		except code SR9 (Swivel base for co-driver' seat)	
₩ĨAR			AR91.10-D-1000TS
28.2	Install turn plate with front passenger seat attached.	Model 907	
		with code SR9 (Swivel base for co-driver' seat)	
		with code ZU8 (National version for USA)	
₩AR			AR91.10-D-1456TS

Nm Headless screws/bolts: screws/bolts and nuts, coarse-pitch thread

Number	Designation			8.8	10.9
BA00.10-Z-1002-01KOA	M6	Galvanized N	lm	9	13
		Phosphated N	lm	9	12

Nm Headless screws/bolts: screws/bolts and nuts, coarse-pitch thread

Number	Designation		12.9
BA00.10-Z-1002-01KOA	M6	Galvanized Nm	16
		Phosphated Nm	14



Work instructions

Van

Group 72 CODE: VS3SCHIEBT

> SM72.16-D-0008D 16.05.2023

Sliding door conversion (code: VS3SCHIEBT, acc. no.: 72 951 62)

Model 907.6/7 with code ZU8 (National version for USA) except code EL9 (Two-way loudspeaker system in front and rear) with electric closing assist of right sliding door

SM72.16-D-0008D	5-D-0008D Sliding door conversion (code: VS3SCHIEBT, acc. no.: 72	
	951 62)	

Model 907.6/7

with code ZU8 (National version for USA) except code EL9 (Two-way loudspeaker system in front and rear) with electric closing assist of right sliding door

Operation no. of the operation texts or standard texts and flat rates

Category	Op. no.	Operation text	Time	Damage Code	Code
L	02 0983	Operations: Modify sliding door on vehicle with code T50, without code EL9/V40	5.1 hrs	72 951 62	VS3SCHIEB T

Important!
On affected vehicles, the sliding door closing assist is removed.
Replacement parts ordering:

Before ordering the required replacement parts, the special equipment code T50 (Electrical closing assist for right sliding door) must be removed from the Vehicle Documentation (VeDoc). Only then can the correct replacement parts can be determined using XENTRY Parts Information.

Vehicle documentation (VeDoc):

Changes in VeDoc can only be made by users with write permission.

If no-one with change authorization is available, a ticket must be created in the "XENTRY Support and Feedback (XSF)" system for "Vehicle data/VeDoc".

Please note that the XSF ticket has to be approved by the national organization, something which involves additional processing time.

It may take a few days for the entry to be visible in VeDoc.

In the event of problems:

If problems arise while carrying out the service measure, please create a PTSS case.

To do this, use the "DTS pre-case checklist".

The most recent version is always available via the XENTRY Portal.

4 Cover



D72.16-A044-72



8 Closing assist motor electrical wiring harness

- 9 Blind plug
- 13 Connector
- 14 Connector




D72.16-A046-82

<u>∧</u> Warning	Risk of injury caused by fingers being jammed or pinched when removing, installing or aligning hoods, doors, trunk lid/rear-end door or sliding roof.	No parts of the body or limbs should be within the operating area when the components are moving.	AS00.00-Z-0011-01A
<u>∧</u> Caution	Risk of injury caused by scraping or cutting body parts on sharp vehicle parts	Always wear protective gloves when working on or near sharp and non-deburred vehicle parts. Deburr repair panels.	AS00.00-Z-0017-01A
Notice	Information on preventing damage to electronic components due to electrostatic discharge		AH54.00-P-0001-01A
Notice	Notes on carrying out repair work in the vehicle interior		AH68.00-D-0001-01KOS
Notice	Notes on retrofitting electrical/ optical lines		AH82.00-P-0000-01A
4	Check		
1	Check if vehicle is affected by measure.		

	Update Vehicle Documentation (VeDoc)		
2	Remove special equipment from online vehicle data card.	i Remove existing code T50 (Electrical actuation for right sliding door).	
3	Attach "Sliding door converted as per SM72.16-D-0008D note" under field organization texts to KG72.		
X	Remove		
4	Detach ground line of on-board electrical system battery.		
⊯FAR			AR54.10-D-0029TS
5	Remove component parts in vehicle interior for sliding door conversion.		Page 24
6	Remove cover(4).	i To do this, unscrew screw/bolts. Cover (4) is no longer required.	
7	Remove closing assist motor with lock striker in C-pillar.		
₩FAR		i The closing assist motor is no longer required.	AR72.16-D-0002TSR
8	Remove lower guide rail for sliding door.		
₩FAR		Model 907.6/7 i The lower carriage is no longer required.	AR72.16-D-7816TS
9	Remove closing assist motor electrical subharness (8).	 i To do so, unclip electrical subharness (8), guide it out of C-pillar then disconnect electrical connector. i The electrical subharness (8) is no longer required. G' Clip remover 	452 589 01 63 00
10	Install blind plugs (9) into plug (13).	i A 048 545 42 28 A 000 545 78 80	
11	Connect plug (13) to plug (14).		
12	Strap down plug (14) using cable ties on factory-installed electrical wiring harness or at suitable point.	i The plug (14) is no longer required. Information on wiring diagram: Right sliding door electrical connector 3 (B-pillar) (100/11x3)	

	Modify sliding door		
13	Remove electric sliding door		
	control unit.		
₩AR			AR72.29-D-5898TS
		i	
		The control unit is no longer	
		required.	
14	Retrofit electrical wiring harness in		Page 8
4.5	sliding door.		Dawa 0
15	Modify detachable parts on sliding door.		Page 8
		i	
		Operation steps 3 to 8 of document	
		reference.	
	Retrofit wiring harness in		
	vehicle interior		
16	Fabricate wiring harness for sliding		
	door.		
₩ PE	Wiring diagram for sliding door		PE72.16-D-2001LAA
			Page 19
		S Wiring harness repair kit, basic	000 589 13 99 00
17	Retrofit wiring harness for sliding door.		
r~~~~~	000 588 00 84 00 Heat gun		WS54.00-P-0049B
₩¥₩S	Repairing wiring harness using		AR00.19-P-0100-09A
₩ AR	solder connectors		
₩PE	Wiring diagram for sliding door		PE72.16-D-2001LAA
			Page 12
		S Reflector	220 589 01 99 41
		S Adapter	220 589 01 99 42
		S Wiring harness repair kit, basic	000 589 13 99 00
X	Install		
18	Install new lower sliding door		
	carriage.		
₩ĨAR		Model 907.6/7	AR72.16-D-7844TS
19	Install lower guide rail for sliding		
	door.	M + 1 007 0/7	
₩ AR		Model 907.6/7	AR72.16-D-7816TS
20	Retrofit reinforcement for lock		Page 22
21	striker in C-pillar. Install removed component parts		Page 24
<u>کا</u>	in vehicle interior for sliding door		raye 24
	conversion.		
22	Connect ground line of on-board		
	electrical system battery.		
🖛 A R			AR54.10-D-0029TS


	SCN coding		
23	Connect diagnostic system.		AD00.00-D-2000-06TS
₩AD		i It is absolutely essential to precisely follow the operation steps as described in the vehicle diagnosis system.	
24	Connect charging equipment.		
₩ AR		During the entire work procedure a sufficiently large voltage supply must be provided for the vehicle's on-board electrical system.	AR54.10-D-1127TS
		Otherwise any undervoltage that occurs may damage the control units. i Follow the operating instructions for the charger.	
		i Use the charger to ensure that an adequate power supply (min. 12.5 V) is provided for the on- board electrical system battery.	
25	Perform SCN coding on signal acquisition and actuation module (SAM) control unit.		
₩ ^S AR		i Under the "Control unit adaptations" menu item, follow the instructions for "SCN coding".	AR54.21-D-0015TS
26	Remove charger from vehicle.		
₩ AR			AR54.10-D-1127TS
4	Check		
27	Check sliding door for correct opening and closing.	i See Operator's Manual.	



Adapter


220 589 01 99 41

Reflector



Wiring harness repair

kit, basic



Clip remover

Parts ordering note


Part no.	Designation	Quantity
A 907 540 8965 07	Electrical wiring harness for manual sliding door for vehicles WITHOUT EL9	1
A 906 630 33 00	C-pillar	1
A 906 720 02 04	Lock striker	1
A 000 984 31 29	Screw	2
A 000 995 51 14	Line fastener	5
N 000000 000455	Screw	2
A 906 692 12 22 9051	Cover (on vehicle with code V36 Roof lining)	2
A 906 692 07 22 9051	Cover	1
A 910 998 02 50 9051	Cover plug	n. B.
A 910 998 00 50 9051	Cover plug	n. B.
A 037 545 35 28	Plug-in connector	1
A 048 545 42 28	Connector	1
A 000 545 78 80	Blind plug	12
	Parts for electrical wiring harness:	
	Electric lines (available on free market, observe specifications)	4
A 013 545 76 26	Female contact	1
A 001 982 57 02	Cable lug (ground connection)	1
A 009 545 81 26	Female contact	4
A 037 545 34 28	Connector	1
A 000 995 25 94	Cable tie	n. B.

Part Number	Description	Qty
A9078213000	Contact Strip/Switch	1
N00000000455	Tapping screw; Contact Switch mount; 4,2X19	2
A0009906425	Clip nut for tapping screw	2
A9078213100	Contact Plate	1
A0009903111	Pan Head Screw; Contact Plate mount; 5X14	2

SM72.16-D-0008-01SGB	Convert sliding door (code: VS3SCHIEBT, acc. no.: 72 951 62)		
----------------------	--	--	--

Model 907.6/7


with code ZU8 (National version for USA) with electric closing assist of right sliding door



Clip remover

Refit electrical wiring harness

Shown on model 907.7 with code EL9 (2-way speaker system, front and rear)



D72.16-A049-76

1 Remove electrical wiring harness (28).


i

To do so, unclip electrical wiring harness (28) from sliding door (23). 🔗

The number of fastenings can vary here, depending on the equipment installed.

i

The electrical wiring harness (28) is no longer required.



Shown on model 907.7 with code EL9 (2-way speaker system, front and rear)


2 Install new electrical wiring harness (29) as shown.

i Order electrical wiring harness (29) in accordance with parts catalog DG 82.607.

i

Continue in the higher-level service document.

Modify sliding door detachable parts



4

5

D72.16-A079-79

3 Remove lower carriage (42) from sliding door.

i For this purpose, remove screws (43).

i


The removed lower carriage (42) is no longer required.

6


Remove cover (46).

To do this, remove screws (47).

- Release cable duct (44) (arrow) and remove from lower sliding carriage (42).
- Remove cable duct (44) with electrical wiring harness (45).



D72.16-A081-81



- 7 Connect contact switch (48) to plug connector (49) of new electrical wiring harness (29).
 - Install contact switch (48) A9078213000

8

i To do so, turn in screws (47) N00000000455

SM72.16-D-0008D / Van / 16.05.2023

SM72.16-D-0008-02SG	Retrofit wiring harness for sliding door (code: VS3SCHIEBT, acc. no.: 72 951 62)	
Notice	Information on preventing damage to electronic components due to electrostatic discharge	AH54.00-P-0001-01A
Notice	Notes on carrying out repair work in the vehicle interior	AH68.00-D-0001-01KOS
₩S	000 588 00 84 00 Heat gun	WS54.00-P-0049B
₩ĨAR	Repairing wiring harness using solder connectors	AR00.19-P-0100-09A
₩ PE	Wiring diagram for sliding door	PE72.16-D-2001LAA

Model 907.6/7


with code ZU8 (National version for USA) except code EL9 (Two-way loudspeaker system in front and rear)

Nm Headless screws/bolts: screws/bolts and nuts, coarse-pitch thread


Number	Designation			8.8	10.9
BA00.10-Z-1002-01KOA	M6	Galvanized N	١m	9	13
		Phosphated N	١m	9	12

Nm Headless screws/bolts: screws/bolts and nuts, coarse-pitch thread


Number	Designation			12.9
BA00.10-Z-1002-01KOA	M6	Galvanized	Nm	16
		Phosphated	Nm	14



Adapter



Wiring harness repair kit, basic




Reflector

٤!)

Do not kink any electric lines and ensure that they are routed without any chafing.

This prevents any damage.



D72.16-A037-78

Route electrical wiring harness (1)

i

The following specified line colors for the electric lines correspond to the series production configuration.

- 1 Route electric lines "YE/GN", "BN", "BU/ BK", as shown.
- 2 Join electric lines "YE/GN", "BN", "BU/ BK", "BU/BN" and wrap, section-bysection, with suitable insulation tape.

i


The electrical wiring harness (1) is made up of the electric lines "YE/GN", "BN", "BU/BK", "BU/BN".

Make sure that the junctions of the electric lines "YE/GN", "BN", "BU/BK", "BU/BN" remain free at the connection end.

3

Loosely fasten electrical wiring harness (1) in sections at factory-installed electrical wiring harness or at a suitable position using cable ties.

Electrical wiring harness (1) to end sleeves



D72.16-A038-75

4 Disconnect control circuit 1 central locking end sleeve (Z21/16) from electrical wiring harness (5).

Electric line "BU/BK".

Connect electric line "BU/BK" of electrical wiring harness (5) and electric line "BU/BK" of electrical wiring harness (1) to new end sleeve (6).

i

5

To do so, use heat gun with \Im reflector or \Im adapter.

S Use basic wiring harness repair kit.

Disconnect control circuit 1 central locking end sleeve (Z21/17) from electrical wiring harness (5).



6

7

Electric line "BU/BN".

Connect electric line "BU/BN" of electrical wiring harness (5) and electric line "BU/BN" of electrical wiring harness (1) to new end sleeve (6).

i

To do so, use heat gun with \Im reflector or \Im adapter.


S Use basic wiring harness repair kit.

Electrical wiring harness (1) to signal acquisition and actuation module (SAM) control unit


8 Release and disconnect electrical connector (RBA1) from SAM (N10).



D72.16-A039-76







D72.16-A040-78

Disassemble electrical connector (RBA1).

i

9

To do so, release plug housing (arrows A), guide out plugs (7, 8) and disconnect from each other.

10 Install electric line "YE/GN" of electrical wiring harness (1) into contact cavity 42 of plug (8). 11

Assemble electrical connector (RBA1).

 i

 To do so, connect plugs (7, 8) and guide

into plug housing, then lock.


12 Use cable ties to fasten electric line "YE/GN" directly behind plug housing of electrical connector (RBA1) to factoryinstalled electrical wiring harness.

- 13 Strap down extended length of electric line "YE/GN" at suitable point.
- 14 Connect electrical connector (RBA1) to SAM control unit (N10).



D72.16-A039-76

Electrical wiring harness (1) to "Right sliding door contact plate 1 electrical connector (X100/1)" (plug (9))



D72.16-A041-75

15 Release plug (9) (arrow B). i A 048 545 42 28 Plug


16 Install contact sockets (4) in plug (9).

i

Contact cavity 1: Electric line **"YE/GN"** Contact cavity 3: Electrical line **"BN"** Contact cavity 4: Electrical line **BU/BN** Contact cavity 5: Electrical line **"BU/BK"**


17 Lock plug (9).

Electrical wiring harness (1) to ground connection



D72.16-A042-11

- 18 Remove nut of driver seat base ground point 1 (W105/1).
- 19 Connect cable lug (3) of electrical wiring harness (1) to driver seat base ground point 1 (W105/1).
- 20 Attach nut of driver seat base ground point 1 (W105/1) Nm.




D72.16-A037-78

Tighten electrical wiring harness (1)

21 Tighten loosely attached cable ties on complete electrical wiring harness (1). If necessary,

↓ Strap down extended length of electrical wiring harness (1) at a suitable point. 22


Install contact plate (38) A9078213100 i To do so, connect plug (9) and screw in screws A0009903111



D72.16-A059-75

SM72.16-D-0008-03SG	Fabricate wiring harness for sliding door (code: VS3SCHIEBT, acc. no.: 72 951 62)	
Notice	Information on preventing damage to electronic components due to electrostatic discharge	AH54.00-P-0001-01A
Notice	Notes on carrying out repair work in the vehicle interior	AH68.00-D-0001-01KOS
Notice	Notes on retrofitting electrical/ optical lines	AH82.00-P-0000-01A
₽₽	Wiring diagram for sliding door	PE72.16-D-2001LAA


Model 907.6/7 with code ZU8 (National version for USA)



Wiring harness repair kit, basic

i

The following specified line colors for the electric lines correspond to the series production configuration and they can be replaced, if necessary, with similar line colors. Please ensure that electrical lines can be correctly assigned in accordance with slot assignment.



```
D72.16-A036-79
```

1	Prepare electric line "YE/GN". i X100/1 to RBA1 Line color "YE/GN" Length approx. 410 cm Cross section 0.5 mm ²		i X100/1 to Z21/17 Line color "BU/BN" Length approx. 232 cm Cross section 0.75 mm ²
2	Prepare electric line "BN". i X100/1 to W105/1 Line color "BN" Length approx. 255 cm Cross section 0.5 mm ²	5	Crimp contact socket (2) onto electric line "YE/GN". Use basic wiring harness repair kit. A 013 545 76 26 Contact socket
3	Prepare electric line "BU/BK". i X100/1 to Z21/16 Line color "BU/BK" Length approx. 232 cm Cross section 0.75 mm ²	6	Crimp cable lug (3) onto electric line "BN". i 3 Use basic wiring harness repair kit. i A 001 982 57 02 Cable lug
4	Prepare electric line "BU/BN".	7	Crimp contact sockets (4) on one side onto electric lines "YE/GN", "BN", "BU/ BK", "BN/BN". <u>i</u> S' Use basic wiring harness repair kit.

i A 009 545 81 26 Contact socket A 001 545 78 80 Seal

8

Attach note in online vehicle data card under field organization texts to KG72. If line colors of prepared wiring harness (1) deviate from series production configuration.

i

Note:

Line colors of retrofitted wiring harness for sliding door deviate from series production configuration.

SM72.16-D-0008-04SG	Retrofit reinforcement for lock striker in C-pillar (code: VS3SCHIEBT, acc. no.: 72	
	951 62)	

Model 907.6/7 with code ZU8 (National version for USA)

1


Remove reinforcement (38) from C-pillar new part.

i

To do so, bend reinforcement (38) slightly in upper area (arrow). This makes removal easier.


i

The new C-pillar part is not required and should be disposed of properly.



D72.16-A078-82

2 Install reinforcement (38) on C-pillar (40).



D72.16-A071-76



D72.16-A080-75


3

Install lock striker (41). i Tighten screws slightly by hand. Screws are tightened when adjusting sliding door.

SM72.16-D-0009SG	Prepare vehicle interior at front for sliding door conversion	
	(code: VS3SCHIEBT, acc. no.: 72 951 62)	

Model 907

with code ZU8 (National version for USA)



51 Control unit bracket 52 Nut

D54.21-A026-09

Shown on model 907.7 without S23 (Front passenger bench seat)


- 10 Cover
- 11 Nuts
- 12 Air duct



D31.19-1216-12

Shown on model 907.7 without S23 (Front passenger bench seat)

- 15 Air duct
- 16 Nuts
- 17 Cable duct
- 18 Bolts
- 19 Battery cover
- 20 Cover



D31.19-1217-06

<u>∧</u> Warning	Risk of injury caused by fingers being jammed or pinched when removing, installing or aligning hoods, doors, trunk lid/rear-end door or sliding roof.	No parts of the body or limbs should be within the operating area when the components are moving.	AS00.00-Z-0011-01A
<u> </u>	Risk of injury caused by scraping or cutting body parts on sharp vehicle parts	Always wear protective gloves when working on or near sharp and non-deburred vehicle parts.	AS00.00-Z-0017-01A
		Deburr repair panels.	
Notice	Information on preventing damage to electronic components due to electrostatic discharge		AH54.00-P-0001-01A
Notice	Notes on carrying out repair work in the vehicle interior		AH68.00-D-0001-01KOS
Notice	Notes on retrofitting electrical/ optical lines		AH82.00-P-0000-01A
X	Remove		
1.1	Remove driver seat.	Model 907	
		with code ZU8 (National version for USA)	
		except code SR8 (Swivel base for driver' seat)	
₩ĨAR			AR91.10-D-1000TS
1.2	Remove turn plate with mounted driver's seat.	Model 907	
		with code SR8 (Swivel base for driver' seat)	
		with code ZU8 (National version for USA)	
₩			AR91.10-D-1456TS
		i Do not separate driver's seat from turn plate.	
2	Remove seat base cover from driver's seat.		

3	Remove control unit holder (51).	If control unit holder (51) is installed.	
		i i	
		To do so, remove nut (52).	
		Position control unit holder (51) so that ground points are accessible.	
		The number of control units varies	
		depending on the vehicle equipment.	
		If control units are installed in control unit holder (51),	
		Ļ	
		unclip control units.	
		i	
		Do not disconnect plugs of control units.	
4.1	Remove front passenger seat.	Model 907	
		with code ZU8 (National version for USA)	
		except code SR9 (Swivel base for co-driver' seat)	
			AR91.10-D-1000TS
₩ AR 4.2	Remove turn plate with installed	Model 907	
4.2	front passenger seat.		
		with code SR9 (Swivel base for co-driver' seat)	
		with code ZU8 (National version for USA)	
₩ĨAR			AR91.10-D-1456TS
AK		ī	
		Do not disconnect front passenger seat from turn plate.	
5	Remove seat base cover of front passenger seat.		
6	Remove front floor coverings.		
₩₹AR			AR68.80-D-0006TSR
7	Remove vehicle tool kit carrier plate.		
₩ĨAR			AR68.30-D-5021TS
8	Remove lower A-pillar trim on front passenger side.		
₩AR			AR68.30-D-0012TSR
9	Remove cover (10).		
10	Remove air duct (12).	i	
		For this purpose, remove nuts (11).	
11	Remove air duct (15).		

10			
12	Remove cable duct (17).	i To do so, remove nuts (16).	
13	Remove battery cover (19).	i To do so, remove screws (18).	
14	Release cover (20).	i Release cover (20) using a suitable screwdriver (arrows). Release cover (20) until wiring harness can be routed.	
X	Install		
15	Install cover (20).		
16	Install battery cover (19).	i To do so, tighten the screws (18).	
17	Install cable duct (17).	i To do so, attach nuts (16). Nm M6	BA00.10-Z-1002-01KOA
18	Install air duct (15).		
19	Install air duct (12).	i To do this, attach nuts (11). Nm M6	BA00.10-Z-1002-01KOA
20	Install cover (10).		
21	Install vehicle tool kit carrier plate.		
₩ĨAR			AR68.30-D-5021TS
22 ⊯ ∽A R	Install front floor coverings.		AR68.80-D-0006TSR
23 F AR	Install lower A-pillar trim on front passenger side.		AR68.30-D-0012TSR
24	Attach control unit holder (51).	If control unit holder (51) is installed. () Do not kink subharness during installation of control unit holder (51) and ensure that it is routed free of chafing. This prevents any damage. I To do so, attach nut (52). The number of control units varies depending on the vehicle equipment. Nm M6 If control units are installed in control unit holder (51), ↓	BA00.10-Z-1002-01KOA
25	Install seat base cover of driver's seat.	clip in control units.	

26.1	Install driver seat.	Model 907	
		with code ZU8 (National version for USA)	
		except code SR8 (Swivel base for driver' seat)	
₩ĨAR			AR91.10-D-1000TS
26.2	Install turn plate with driver's seat attached.	Model 907	
		with code SR8 (Swivel base for driver' seat)	
		with code ZU8 (National version for USA)	
₩ĨAR			AR91.10-D-1456TS
27	Install seat base cover of front passenger seat.		
28.1	Install front passenger seat.	Model 907	
		with code ZU8 (National version for USA)	
		except code SR9 (Swivel base for co-driver' seat)	
₩ĨAR			AR91.10-D-1000TS
28.2	Install turn plate with front passenger seat attached.	Model 907	
		with code SR9 (Swivel base for co-driver' seat)	
		with code ZU8 (National version for USA)	
₩AR			AR91.10-D-1456TS

$\ensuremath{\mathbb{N}}\xspace{\ensuremath{\mathbb{N}}}\xspace{\ensuremath{\mathbb{N}}}$ Headless screws/bolts: screws/bolts and nuts, coarse-pitch thread

Number	Designation			8.8	10.9
BA00.10-Z-1002-01KOA	M6	Galvanized	Nm	9	13
		Phosphated I	Nm	9	12

Nm Headless screws/bolts: screws/bolts and nuts, coarse-pitch thread

Number	Designation		12.9
BA00.10-Z-1002-01KOA	M6	Galvanized Nr	า 16
		Phosphated Nr	า 14